

County Surveyor's Record, Douglas County, Oregon

18531

Subdivision of Section 3,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
20.005	<p>A fir, 9 ins. diam., bears N. 15½° W., 31 lks. dist., with scribe marks ¼ S3 LS 1987 BT visible on a partially healed blaze.</p> <p>From this point a point established by person(s) unknown, bears N. 70° E., 0.05 chs. dist., monumented with an iron rod, ¾ in. diam., firmly set, projecting 2 ins. above ground.</p> <p>N. 0° 52' 30" W., on the N. and S. center line of sec. 3.</p> <p>Ascend SE. slope, through reproduction timber and dense undergrowth.</p> <p>The center S 1/16 sec. cor. of sec. 3, established and recorded by Orrin K. Frederick, Registered Land Surveyor No. 1987, in 1985, and is accepted as the corner; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 13 ins. above ground, with aluminum cap mkd. LS 1985 S 1/1 S3 1985 CC with a vertical line, from which bearing trees mkd. by Frederick:</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 82½° E., 31 lks. dist., with scribe marks CS 1/16 S3 LS 1987 BT visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 11½° W., 40 lks. dist., with scribe marks CS 1/16 S3 LS 1987 BT visible on a partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> C S 1/16 S 3 C 1986 </div> <p>Deposit the iron rod inside and a white "DEEP-1" magnetic marker at base of the stainless steel post.</p> <p>N. 0° 53' 00" W., beginning new measurement.</p> <p>Ascend S. slope.</p>
9.40	Dirt road, 20 lks. wide, bears N. 80° W. and S. 80° E.
12.00	Dirt road, 30 lks. wide, bears N. 80° E. and S. 80° W.
20.020	<p>The center ¼ sec. cor. of sec. 3, established and recorded by Orrin K. Frederick, Registered Land Surveyor No. 1987, in 1985, and is accepted as the corner; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 10 ins. above ground, with aluminum cap mkd. LS 1987 T32S R6W C¼ S3 1985, from which bearing trees mkd. by Frederick:</p> <p style="padding-left: 40px;">A cedar, 6 ins. diam., bears S. 21½° W., 62 lks. dist., with scribe marks C¼ S3 LS 1987 BT visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 59 ¾° W., 23½ lks. dist., with scribe marks C¼ S3 LS 1987 BT visible on a partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T 32 S R 6 W C ¼ S 3 1986 </div>