

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 3,
T. 32 S., R. 6 W., Willamette Meridian, Oregon 18582

CHAINS	
	<p>Deposit the iron rod inside and a white "DEEP-1" magnetic marker at base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 55' 30" W., beginning new measurement.</p> <p>Descend broken N. slope.</p>
36.40	Gravelled road, 30 lks. wide, bears N. 60° W. and S. 60° E.
36.60	Enter timber, edge bears N. 60° W. and S. 60° E.
39.220	The ¼ sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.
40.235	<p>From the ¼ sec. cor. of secs. 2 and 3.</p> <p>S. 89° 41' 30" W., on the E. and W., center line of sec. 3.</p> <p>Ascend steep NE. slope, through heavy timber and moderate undergrowth.</p> <p>The center ¼ sec. cor. of sec. 3.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 40' 30" W., beginning new measurement.</p> <p>Ascend gradually across S. slope.</p>
1.35	Descend SW. slope.
5.70	Dirt Road, 30 lks. wide, bears N. 20° E. and S. 20° W.
38.620	<p>The ¼ sec. cor. of secs. 3 and 4, perpetuated and recorded by the Douglas County Surveyor's Office in 1967, further perpetuated and recorded by Orrin K. Frederick, Registered Land Surveyor No. 1987, in 1985, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 32 S. R 6 W</p> <p>¼ S 4 S 3</p> <p>1967</p> </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A root hole, bears S. 82° E., 9 lks. dist., with a dead and down fir, 30 ins. diam., lying alongside, with an open blaze, no marks visible.</p> <p style="margin-left: 40px;">A fir stump, 48 ins. diam., bears N. 70° W., 25 lks. dist., with axe marks visible on the bark.</p> <p>and bearing trees mkd. by the County Surveyor's Office in 1967</p> <p style="margin-left: 40px;">A yew, 10 ins. diam., bears S. 34° E., 34½ lks. dist., with scribe marks ¼ S3 CS BT visible on a partially healed blaze.</p> <p style="margin-left: 40px;">A fir, 16 ins. diam., bears N. 31° W., 25½ lks. dist., with healed blaze.</p>
8.35	<p>From the S 1/16 sec. cor. of secs. 2 and 3.</p> <p>S. 89° 15' 30" W., on the E. and W. center line of the SE¼ of sec. 3.</p> <p>Ascend NE. slope, through moderate timber and undergrowth.</p> <p>Top of ascent, slopes NW.; desc. SW. slope.</p>