

# County Surveyor's Record, Douglas County, Oregon

18583      Subdivision of Section 3,  
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
16.20	Leave timber, edge bears N. and S.; thence across broken S. slope.
40.040	The center S 1/16 sec. cor. of sec. 3.
Subdivision of Section 10, T. 32 S., R. 6 W., Willamette Meridian, Oregon	
	From the ¼ sec. cor. of secs. 10 and 15.  N. 1° 29' 30" E., on the N. and S. center line of sec. 10.  Ascend SW. slope, through heavy timber and undergrowth.
3.90	Spur, slopes W.; desc. along NW. slope.
19.640	The center S 1/16 sec. cor. of sec. 10, established and recorded by Lloyd D. Smith, Registered Land Surveyor No. 1101, in 1983 and is accepted as the corner; monumented with an aluminum post, 1½ ins. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd.
	STATE OF OREGON C S 1/16   S 10 C 1983 LS 1101 DEPARTMENT OF FORESTRY
	from which bearing trees mkd. by Smith  A chinkapin, 13 ins. diam., bears N. 88° W., 24 lks. dist., with scribe marks CS 1/16 S10 BT visible on a partially healed blaze.  A madrone, 13 ins. diam., bears N. 2 3/4° W., 33½ lks. dist., with scribe marks CS 1/16 S10 BT visible on a partially healed blaze.
	<hr style="width: 20%; margin: auto;"/> N. 1° 29' 30" E., beginning new measurement.
	Descend NW. slope, through heavy timber and undergrowth.
19.640	The center ¼ sec. cor. of sec. 10, established and recorded by Lloyd D. Smith, Registered Land Surveyor No. 1101, in 1983, and is accepted as the corner; monumented with an aluminum post, 1½ ins. diam., firmly set, projecting 5 ins. above ground, with aluminum cap mkd.
	STATE OF OREGON T 32 S R 6 W C ¼ S 10 1983 SL 1101 DEPARTMENT OF FORESTRY
	from which bearing trees mkd. by Smith  A fir, 8 ins. diam., bears N. 77½° E., 10 lks. dist., with illegible scribe marks visible on a partially healed blaze.  A fir, 18 ins. diam., bears N. 54½° W., 17½ lks. dist., with illegible scribe marks visible on a partially healed blaze.