

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 14,  
T. 32 S., R. 6 W., Willamette Meridian, Oregon

18586

CHAINS	
	<p>A fir, 9 ins. diam., bears S. 25 3/4° E., 46½ lks. dist., mkd. CS 1/16 S14 BT.</p> <p>A fir, 13 ins. diam., bears N. 41 3/4° W., 69½ lks. dist., mkd. CS 1/16 S14 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base and a steel fence post alongside the stainless steel post.</p> <p>The corner is located on NE. slope.</p> <p>Descend across NE. slope.</p>
27.40	Slope changes to E.
38.50	Dirt road, 20 lks. wide, bears N. 20° W. and S. 20° E.
39.320	<p>Point for the center ¼ sec. cor. of sec. 14, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 6 W C ¼ S 14 1986</p> <p>from which</p> <p>A fir, 14 ins. diam., bears S. 50° W., 63½ lks. dist., mkd. C ¼ S14 BT.</p> <p>A fir, 12 ins. diam., bears N. 1¼° W., 56 lks. dist., mkd. C ¼ S14 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Continue descent along E. slope.</p>
43.90	Bottom of descent and S. edge of pond, edge bears N. 50° W. and S. 50° E.; thence across pond.
47.60	North edge of pond, bears N. 25° W. and S. 25° E.; asc. along a gradual W. slope.
48.25	Across nearly level land.
59.80	Creek, 2 lks. wide, course S. 40° W.; asc. along a gradual E. slope.
79.005	The ¼ sec. cor. of secs. 11 and 14.
	<p>From the ¼ sec. cor. of secs. 13 and 14, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 6 W S 14   S 13 1980</p> <p>from which bearing trees mkd. by Aanrud</p> <p>A madrone, 8 ins. diam., bears N. 57½° E., 11 lks. dist., with scribe marks ¼ S13 BT visible on a partially healed blaze.</p>