

# County Surveyor's Record, Douglas County, Oregon

18592

CHAINS

A fir stump, 25 ins. diam., bears S. 14 1/2° E., 36 lks. dist., with scribe marks 1/4 S20 RE 4079 visible on the bark blaze. (Record, N. 30° E., 26 lks.; Lecklider, S. 30° E., 26 lks.)

A fir, 20 ins. diam., bears S. 89° W., 7 lks. dist., with healed double blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, directly over the iron rod, in a rock collar, 3 ft. base, 1 ft. high, with brass cap mkd.

T 27 S R 3 W  
           1/4  
 S 19 | S 20  
           1987

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Corner is located 25 lks. N. of a creek, 2 lks. wide, course S. 85° E.

N. 0° 00' 30" W., bet. secs. 19 and 20, marking and blazing the true line.

Ascend over SE. slope, along a N. and S. timberline, timber to W. and clearcut to E.

9.90 Spur, slopes N. 80° E.; desc. over broken NE. slope.

29.35 Creek, 7 lks. wide, course N. 85° E.; asc. over SE. slope.

33.60 Spur, slopes E.; desc. over NE. slope, also enter Fall Creek Fire area, edge bears NW. and SE.

37.10 Gravelled road, 25 lks. wide, bears N. 30° W. and S. 30° E.

39.985 The cor. of secs. 17, 18, 19 and 20, reestablished and recorded by G. Robert Lecklider, Registered Engineer No. 4079, in 1960, from topography calls to creeks, N., S., And E., and is accepted as the best available evidence of the original corner positions; monumented with an iron rod, 1/2 in. diam., firmly set, projecting 12 ins. above ground, with an aluminum cap, 1 in. diam., mkd. PROPERTY CORNER, from which the remains of the bearing trees mkd. by Lecklider:

A hemlock, 8 ins. diam., bears N. 21 1/2° E., 52 lks. dist. with partially healed burned blaze.

A root hole, bears S. 5° W., 64 lks. dist., with a burned down fir alongside, 46 ins. diam., no marks visible.

A burned cedar snag, 25 ins. diam., bears N. 21° W., 80 lks. dist., no marks visible.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the iron rod, with brass cap mkd.

T 27 S R 3 W  
       S 18 | S 17  
       S 19 | S 20  
           1987

from which a new bearing tree