

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

18593

CHAINS

A burned hemlock snag, 8 ins. diam., bears S. 3 1/2° W.,
16 lks. dist., mkd. T27S R3W S19 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

The Corner is located in the Fall Creek Fire area.

From this point, the United States Coast and Geodetic Survey triangulation station "LANE 1953" bears S. 47° 58' 31" W., 147.514 chs., dist., monumented with a brass tablet, 3 1/2 ins. diam., set in a concrete post, 7 x 7 ins. square, projecting 7 ins. above ground, with top mkd. LANE 1953 and a triangle.

From the cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

| | | | | |
|---|------|------|------|------|
| T 27 S R 3 W | | | | |
| <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 17</td> <td style="padding: 0 5px;">S 16</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 20</td> <td style="padding: 0 5px;">S 21</td> </tr> </table> | S 17 | S 16 | S 20 | S 21 |
| S 17 | S 16 | | | |
| S 20 | S 21 | | | |
| 1958 | | | | |

From which the remains of original bearing trees

A root hole, bears N. 35° E., 20 lks. dist., with a down chinquapin alongside, 14 ins. diam., no marks visible.

A root hole, bears S. 55° E., 11 lks. dist.

and the remains of bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1958

A burned cedar snag, 19 ins. diam., bears N. 88° E.,
71 lks. dist., no marks visible.

A root hole bears S. 71° E., 39 lks. dist.

and the remains of bearing trees mkd. by Corbin

A root hole, bears N. 77 1/2° E., 99 lks. dist.

A burned cedar snag, 12 ins. diam., bears S. 8 1/2° E.,
58 lks. dist., no marks visible.

A sawed, burned fir stump, 30 ins. diam., bears
S 39 1/2° W., 32 lks. dist., no marks visible.

A sawed burned fir stump, 18 ins. diam., bears
N. 16 1/2° W., 65 lks. dist., with scribe marks 7 S R3W
visible on opened blaze. (Record N 23 1/2° W.)

The corner is located in the Fall Creek Fire area.

N. 84° 05' 00" W., bet. secs. 17 and 20.

Descend over broken SW. slope, through burned timber.

2.40 Gravelled road, 30 lks. wide, bears NW. and SE.

7.30 Creek, 4 lks. wide, course N. 55° W.; asc. over broken NE. slope.

22.15 Spur, slopes N. 5° W.; desc. over broken NW. slope, also gravelled road, 25 lks. wide, bears N. 5° W. and S. 10° E.