

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,  
 T. 27 S., R. 3 W., Willamette Meridian, Oregon  
**18595**

CHAINS

T 27 S R 3 W  
 $\frac{1}{4}$  S 18  
 S 19  
 1987

from which

A burned fir snag, 18 ins. diam., bears N. 1 1/2° E.,  
 26 lks. dist., mkd. 1/4 S18 BT.

A burned fir snag, 14 ins. diam., bears S. 60° E.,  
 20 lks. dist., mkd. 1/4 S19 Bt.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Ascend over broken SE. slope, changing to a NE. slope.

68.15 Ridge, bears N. 35° E. and S. 35° W.; desc. over NW. slope.

78.080 The cor. of secs. 18 and 19 only, on the W. bdy. of the Tp. monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 27 S  
 R 4 W | R 3 W  
       | S 18  
 S 24 | S 19  
 1958

from which the remains of bearing trees mkd. by Strickler

A burned fir stump, 16 ins. diam., bears N. 51 1/2° E.,  
 36 lks. dist., with scribe marks R3 visible on  
 burned blaze.

A burned fir stump, 35 ins. diam., bears S. 3° E.,  
 113 lks. dist., with fragmentary scribe marks  
 visible on burned blaze.

and bearing trees mkd. by Corbin

A fir, 18 ins. diam., bears N. 51° E., 121 lks. dist.,  
 with healed blaze.

A maple 16 ins. diam., bears S. 74 1/4° E., 86 lks. dist.,  
 with scribe marks T27S R3W S19 BT visible on open blaze.

A fir, 21 ins. diam., bears S. 32° W., 48 lks. dist.,  
 with healed blaze.

From the cor. of secs. 17, 18, 19, and 20.

N. 0° 03' 00" W., bet. secs. 17 and 18.

Descend over broken NE. slope, through burned timber.

10.15 Creek, 3 lks. wide, course N. 65° E.; asc. over SE. slope.

15.60 Spur, slopes E.; desc. over broken NE. slope.

20.65 Creek, 2 lks. wide, course N. 80° E.; asc. over SW. slope.

22.50 Spur, slopes SE.; desc. over broken NE. slope.

35.90 Creek, 5 lks. wide, course N. 80° E.; asc. over broken SE. slope.