

County Surveyor's Record, Douglas County, Oregon.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

18597

CHAINS

From this point, a point established by Glenn S. Baughman Registered Land Surveyor No. 536, in 1978, bears S.77° 25' 30" W., 0.306 chs. dist., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. T27S R3W S7 S8 S17 S18 1978 RLS 536.

N. 1° 33' 30" E., bet. secs. 7 and 8.

Ascend over SE. slope, over rock slide.

9.60 Spur, slopes NE.; desc. over broken NE. slope, also old rock quarry.

39.40 Spur, slopes N. 70° E.; desc. over NE. slope.

40.190 The 1/4 sec. cor. of secs. 7 and 8, perpetuated and recorded by Gary L. Langlitz, Deputy County Surveyor, in 1975, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 27 S
1/4
S 7 | S 8
R 3 W
1975

from which the remains of an original bearing tree

A burned fir snag, 26 ins. diam., bears S. 80° E.,
21 lks. dist., no marks visible.

and the remains of the bearing trees mkd. by Corbin

A burned madrone snag, 24 ins. diam., bears S. 84 1/2° E.,
54 lks. dist., with healed blaze.

A burned cedar snag, 23 ins. diam., bears N. 65° W.,
57 lks. dist., with healed blaze.

GENERAL DESCRIPTION

The lands included in the foregoing resurvey are located in the Fall Creek fire area in Douglas County, approximately six and one-half miles south of Glide, Oregon. The elevation ranges from about 1080 feet above sea level near the 1/4 section corner of sections 7 and 8, to approximately 2960 feet above sea level near the corner of sections 18 and 19 only.

The area is drained by Jim Creek, Fall Creek, and their tributaries. The soil is a rocky clay. The timber throughout the area is burned and dead from a forest fire the previous year.

Access is gained via a gravelled road along Jim Creek, with numerous gravelled and dirt roads branching from it into the area.

No mineral deposits were noted along the lines resurveyed. The area is used primarily for timber.

The average of readings in the area gives a value of 19° East for the mean magnetic declination. There is a range of 0° 30' due to local attraction.