

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the South Boundary,  
**18601** T. 21 S., R. 4 W., Willamette Meridian, Oregon

**CHAINS**

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 21 S R 4 W  
 ¼ S 31  
 S 6  
 T 22 S R 4 W  
 1988

*FDOK  
 3/4/83  
 12/94 M. 121-26*

from which a new bearing tree

A fir, 6 ins. diam., bears N. 79° E., 10½ lks. dist.,  
 mkd. ¼ S31 BT.

Deposit iron bolt inside and white "DEEP-1" magnetic marker at base of stainless steel post.

S. 89° 19' 30" W., beginning new measurement.

Ascend over broken NE. slope.

19.495 Point for the W 1/16 sec. cor. of secs. 6 and 31.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 S 31  
 S 6  
 1988

*FDOK  
 12/94 M. 121-26*

from which

A fir, 14 ins. diam., bears N. 6¾° E., 39 lks. dist.,  
 mkd. W 1/16 S31 BT.

A fir, 7 ins. diam., bears S. 18½° W., 31 lks. dist.,  
 mkd. W 1/16 S6 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Ascend over broken NE. slope.

26.90 Spur, slopes N. 30° W.; desc. over NW. slope.

40.140 The cor. of Tps. 21 and 22 S., Rs. 4 and 5 W., perpetuated and recorded by Blaine H. McGillicuddy, Registered Engineer No. 2066, in 1953, from original evidence no longer in existence, further perpetuated and recorded by Bruce A. Shaner, Registered Land Surveyor No. 430, in 1972; monumented with an iron post, 1½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 21 S  
 R S 36 | S 31 R  
 5 S 1 | S 6 4  
 W T 22 S W  
 1972

from which bearing trees mkd. by McGillicuddy

A fir, 35 ins. diam., bears N. 43¼° E., 42 lks. dist.,  
 with healed blaze.

A fir, 37 ins. diam., bears S. 25° E., 9 lks. dist.,  
 with healed blaze.