

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the West Boundary,  
**18603** T. 21 S., R. 4 W., Willamette Meridian, Oregon

**CHAINS**

Blaine H. McGillicuddy, Registered Engineer No. 2066, in 1953, and further perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1964. There is no remaining evidence of the original corner, and this position is accepted as the corner; monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 12 ins. above ground, from which the remaining bearing tree mkd. by Godfrey:

A fir, 18 ins. diam., bears S.  $83\frac{1}{2}^{\circ}$  E., 28 lks. dist., with healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T 21 S  
 R 5 W R 4 W  
 1/4  
 S 36 | S 31  
 1988

from which new bearing trees

A fir, 14 ins. diam., bears S.  $24^{\circ}$  E., 19 lks. dist., mkd. 1/4 S31 Bt.

A fir, 13 ins. diam., bears N.  $46\frac{1}{2}^{\circ}$  W., 28 lks. dist., mkd. 1/4 S36 BT.

Deposit iron pipe alongside and white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, the true point for cor. of secs. 25, 30, 31 and 36, bears N.  $0^{\circ} 43' 30''$  W., 39.860 chs. dist., hereinafter described.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
 T. 21 S., R 4 W., Willamette Meridian, Oregon

(Restoring the survey by Harvey Gordon and Charles T. Gardner in 1855-56, and the resurvey by Peter A. Peterson and Daniel L. Berry in 1971-71)

From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the tp.

N.  $0^{\circ} 46' 30''$  W., bet. secs. 31 and 32.

Descend over broken NE. slope, through heavy timber and dense undergrowth.

20.025 The S 1/16 sec. cor. of secs. 31 and 32, established and recorded by Floyd J. Cole, Deputy County Surveyor, in 1914, and is accepted as the corner; determined at record bearing and distance from the remains of a bearing tree mkd. by Cole:

A sawed fir stump 10 ins. diam., bears N.  $71^{\circ}$  W., 28 lks. dist., with scribe marks BT visible on opened blaze.

At the corner point

Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16  
 S 31 | S 32  
 1988