

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 21 S., R. 4 W., Willamette Meridian, Oregon

18604

CHAINS

from which new bearing trees

A hemlock, 10 ins. diam., bears N. 89° E., 30 lks. dist.,
mkd. S 1/16 S32 BT.

A fir, 26 ins. diam., bears N. 83° W., 29 lks. dist.,
mkd. S 1/16 S31 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

N. 0° 41' 00" W., beginning new measurement.

Descend over broken NE. slope.

8.15 Dirt road, 25 lks. wide, bears N. 30° W. and S. 35° E.; also bottom of descent, drains S. 30° E.; asc. over broken SE. slope.

14.20 Spur, slopes N. 65° E.; desc. over NE. slope.

20.105 The ¼ sec. cor. of secs. 31 and 32, reestablished and recorded by Floyd J. Cole, Deputy County Surveyor, in 1914, and perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1962. There is no remaining evidence of the original corner, and this position is accepted as the corner; monumented with "T" shaped iron rod, 1 in. diam., firmly set, projecting 10 ins. above ground, from which the remains of bearing trees mkd. by Cole:

A sawed cedar stump, 25 ins. diam., bears N. 18° E.,
159 lks. dist., no marks visible.

A sawed fir stump, 18 ins. diam., bears S. 28° E.,
100 lks. dist., no marks visible.

and a bearing tree mkd. by Haines

A fir, 17 ins. diam., bears S. 30° E., 58 lks. dist.,
with healed double blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 21 S R 4 W
 ↓
 S 31 | S 32
 1988

from which a new bearing tree

A fir, 10 ins. diam., bears S. 49° W., 23 lks. dist.,
mkd. ¼ S31 BT.

Deposit T iron inside and white "DEEP-1" magnetic marker at base of stainless steel post.

From this point the cor. of secs. 29, 30, 31, and 32, bears N. 0° 30' 30" W., 40.205 chs. dist., hereinafter described.

From the cor. of secs. 29, 30, 31, and 32, restored by person(s) unknown, recorded by Floyd J. Cole, Deputy County Surveyor, in 1914, and further recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1962. There is no remaining original evidence of the corner, and this position is accepted as the corner; monumented with an iron rod, ¾ in. diam., firmly set projecting 4 ins. above ground, with an iron pipe alongside, 1½ ins. diam., firmly set, buried 14 ins. below surface of ground.