

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 21 S., R. 4 W., Willamette Meridian, Oregon 18608

CHAINS

21.600 Point selected for the witness cor. to E 1/16 sec. cor. of secs. 17 and 20.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.

	WC
E 1/16	S 17
	S 20
	1988

from which

A fir, 30 ins. diam., bears S. 77½° W., 790 lks. dist.,
mkd. X BT.

An oak, 33 ins. diam., bears N. 66¼°, 393 lks. dist.,
mkd. X BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, the Douglas County Horizontal Control Station "HONOR" bears S. 46° 03' 20" W., 140.075 chs. dist., monumented with a brass cap, 3 ins. diam., set in a concrete filled bell tile, 8 ins. diam., flush with the ground, with top mkd. COUNTY SURVEYORS OFFICE HONOR 1978.

Corner is located on the west side of the West guard railing.

23.05 Center line of Southern Pacific Railroad tracks, 10 lks. wide, bears N. 65° E. and S. 65° W.

25.45 County Road No. 212, asphalt surface, 30 lks. wide, bears N. 55° E. and S. 55° W.

33.50 Pass Creek, 15 lks. wide, course S. 20° W.; asc. over gentle SE. slope.

35.00 Gravelled road, 15 lks. wide, bears S. 20° E. and N. 20° W.

39.60 Pass Creek, 15 lks. wide, course N. 20° W.; asc. over NE. slope.

39.800 The ¼ cor. of secs. 17 and 20, monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

	¼ S 17
	S 20
T 21 S R 4 W	
	1971

from which bearing trees mkd. by Peterson and Berry

An alder, 15 ins. diam., bears S. 84° W., 12 lks. dist.,
with healed blaze.

An alder, 10 ins. diam., bears N. 27° W., 50 lks. dist.,
with healed blaze.

From the cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 1½ ins. diam., firmly set, projecting 20 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

	T 21 S	
S 18		S 17
S 19		S 20
	R 4 W	
	1968	