

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a portion of the Subdivisional Lines,
18609 T. 21 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

from which bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1958

A fir, 22 ins. diam., bears N. 84° E., 41 lks. dist., with healed double blaze.

A fir, 31 ins. diam., bears S. 65° E., 27 lks. dist., with healed double blaze.

A madrone, 26 ins. diam., bears N. 73¼° W., 180 lks. dist., with healed blaze. (Record, N. 71° W.)

and a bearing tree mkd. by Vernon R. Tracy, Deputy County Surveyor, in 1968

A fir, 22 ins. diam., bears S. 43¼° W., 79 lks. dist., with healed double blaze. (Record S. 45° W.)

and a bearing tree mkd. by Charles W. Guile, Registered Land Surveyor No. 472, in 1986

A fir, 17 ins. diam., bears N. 73¼° W., 17 lks. dist., with fragmentary scribe marks visible on a partially healed double blaze.

The corner is located at the intersection of fences, extending N., S., E., and W.

N. 0° 30' 30" W., bet. secs. 17 and 18.

Descend over gentle NE. slope, through heavy timber and light undergrowth.

2.50 Ravine, drains E.; asc. over broken SE. slope.

17.90 Spur, slopes E.; desc. along broken E. slope.

20.260 Point for the S 1/16 sec. cor. of secs. 17 and 18.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
 S 18 | S 17
 1989

from which

A fir, 13 ins. diam., bears S. 71° E., 33 lks. dist., mkd. S 1/16 S17 BT.

A fir, 10 ins. diam., bears N. 28° W., 13 lks. dist., mkd. S 1/16 S18 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Descend along broken E. slope.

40.520 The ¼ sec. cor. of secs. 17 and 18, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1969, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
 T 21 S
 ¼ S 18 | S 17
 R 4 W
 1969