

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 17,  
**18611** T. 21 S., R. 4 W., Willamette Meridian, Oregon

**CHAINS**

Deposit white 'DEEP-1" magnetic marker at base of stainless steel post.

From this point, a fence corner bears N. 27 $\frac{1}{4}$ ° E., 0.70 chs. dist., fence extends N. and E.  
 Descend over NE. slope.

48.20 Ravine, drains N. 75° E.; asc. over broken SE. slope.

61.80 Ridge, bears N. 35° E. and S. 35° W.; desc. over NW. slope.

69.15 Head of ravine, drains S. 80° W.; asc. over SW. slope.

71.00 Spur, slopes NW.; desc. over steep NE. slope.

76.65 Creek, 2 lks. wide, course N. 65° W.; asc. over SW. slope.

79.35 Spur, slopes W.; desc. over NW. slope.

80.945 The  $\frac{1}{4}$  sec. cor. of secs. 8 and 17, monumented with an iron post, 18 ins. long, 1 $\frac{1}{4}$  ins. diam., loosely set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
 T 21 S  
 $\frac{1}{4}$  S 8  
 S 17  
 R 4 W  
 1969

from which the remains of an original bearing tree

A fir stump, 48 ins. diam., bears S 74° W., 126 lks. dist., no marks visible on opened blaze.

and bearing trees mkd. by Vernon R. Tracy, Deputy County Surveyor, in 1969. (Record, James W. Byron, Deputy County Surveyor.)

A fir, 26 ins. diam., bears N. 64° E., 39 lks. dist., with healed blaze. (Record, 43 lks.)

A fir, 18 ins. diam., bears S. 29° W., 51 lks. dist., with healed blaze.

At the corner point

Reset the iron post, 6 ins. in drill hole, in solid bedrock, and add the marks RESET 1988 to brass cap.

Corner is located in the bottom of a ravine, drains SW.

From the  $\frac{1}{4}$  sec. cor. of secs. 16 and 17, monumented with an iron post, 2 $\frac{1}{2}$  ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.

T 21 S R 4 W  
 $\frac{1}{4}$   
 S 17 | S 16  
 1972

from which bearing trees mkd. by Peterson and Berry

A fir, 18 ins. diam., bears N. 25° E., 55 $\frac{1}{2}$  lks. dist., with healed blaze. (Record, 57 lks.)

A fir, 13 ins. diam., bears N. 15° W., 88 lks. dist., with healed blaze.

From this point, the S 1/16 sec. cor. of secs. 16 and 17, bears S. 0° 21' 00" E., 19.955 chs. dist., hereinafter described.