

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 17,
T. 21 S., R. 4 W., Willamette Meridian, Oregon 18612

CHAINS	
	N. 89° 18' 30" W., on the E. and W. center line of sec. 17.
	Descend over broken SW. slope, through heavy timber and dense undergrowth.
6.95	Creek, 2 lks. wide, course S. 60° E.; asc. over broken NE. slope.
15.80	Dirt road, 15 lks. wide, bears N. and S.
16.15	Spur, slopes S. 5° E.; desc. over broken SW. slope.
19.825	Point for the center E 1/16 sec. cor. of sec. 17.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="display: flex; justify-content: center; align-items: center;"> C <u>E 1/16</u> C S 17 1988 </div>
	from which
	A fir, 6 ins. diam., bears S. 38° E., 15 lks. dist., mkd. CE 1/16 S17 BT.
	A fir, 8 ins. diam., bears N. 67° W., 54 lks. dist., mkd. X BT.
	Deposit white "DEEP-1" magnetic marker at base of stainless steel post.
	From this point, a point established by person(s) unknown, bears N. 33° 48' E., 0.450 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground, at intersection of fences, extending N., S., and W.
	Descend over broken SW. slope.
28.60	Creek, 2 lks. wide, course S. 30° E.; asc. over SE. slope.
29.25	Spur, slopes S. 30° E.; desc. over SW. slope.
30.10	Creek, 1 lk. wide, course S. 30° E.; asc. over broken SE. slope.
39.650	The center ¼ sec. cor. of sec. 17.
	Ascend over NE. slope.
41.25	Ridge, bears N. 15° E. and S.; desc. over steep W. slope.
56.10	Gravelled road, 25 lks. wide, bears N. 10° E. and S. 10° W.
59.735	Point for the center W 1/16 sec. cor. of sec. 17.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<div style="display: flex; justify-content: center; align-items: center;"> C <u>W 1/16</u> C S 17 1988 </div>
	from which
	A fir, 10 ins. diam., bears S. 80° W., 7 lks. dist., mkd. X BT.
	A fir, 16 ins. diam., bears N. 9° W., 32½ lks. dist., mkd. CW 1/16 S17 BT.
	Deposit white "DEEP-1" magnetic marker at base of stainless steel post.