

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 17,
T. 21 S., R. 4 W., Willamette Meridian, Oregon

18614

CHAINS							
	Ascend over broken SE. slope, through open pasture.						
19.05	Spur, slopes S. 30° E.; desc. over SW. slope.						
19.850	The SE 1/16 sec. cor. of sec. 17.						
	Descend over SW. slope, through heavy timber and dense undergrowth.						
21.10	Creek, 3 lks. wide, course S. 35° E.; asc. over SE. slope.						
34.50	Spur, slopes S. 30° E.; desc. over SW. slope.						
39.710	The center S 1/16 sec. cor. of sec. 17						
<p>From the W 1/16 sec. cor. of secs. 17 and 20, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr> <td style="padding-right: 10px;">W 1/16</td> <td style="border-bottom: 1px solid black;">S 17</td> </tr> <tr> <td></td> <td>S 20</td> </tr> <tr> <td></td> <td>1971</td> </tr> </table> </div> <p>from which bearing trees mkd. by Peterson and Berry</p> <p style="margin-left: 40px;">A fir, 20 ins. diam., bears S. 54° E., 17 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 16 ins. diam., bears N. 4° W., 42 lks. dist., with healed blaze.</p> <p>Corner is 3 lks. W. of fence, extending N. and S.</p> <p>N. 0° 20' 00" W., on the N. and S. center line of the SW¼ of sec. 17.</p> <p>Descend over NW. slope, through heavy timber and dense undergrowth.</p>		W 1/16	S 17		S 20		1971
W 1/16	S 17						
	S 20						
	1971						
4.50	Creek, 6 lks. wide, course N. 65° E.; asc. over SE. slope.						
16.00	Spur, slopes N. 60° E.; desc. over NE. slope.						
20.180	Point for the SW 1/16 sec. cor. of sec. 17, at intersection with the E. and W. center line of the SW¼.						
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.						
	<table style="margin: auto;"> <tr> <td style="padding-right: 10px;">SW 1/16</td> <td style="border-bottom: 1px solid black;">S 17</td> </tr> <tr> <td></td> <td>1989</td> </tr> </table>	SW 1/16	S 17		1989		
SW 1/16	S 17						
	1989						
	<p>from which</p> <p style="margin-left: 40px;">A fir, 32 ins. diam., bears S. 10° W., 16 lks. dist., mkd. SW 1/16 S 17.</p> <p style="margin-left: 40px;">A cedar, 18 ins. diam., bears N. 50½° W., 40 lks. dist., mkd. SW 1/16 S17 BT.</p> <p>From the corner, a down fence corner bears N. 45° E., 0.12 chs. dist.</p> <p>Descend over NE. slope.</p>						
24.35	Creek, 2 lks. wide, course S. 50° E.; desc. over NE. slope.						
25.90	Ward Creek, 15 lks. wide, course N. 85° E.; asc. over broken SW. slope.						