

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 17,  
 18615 T. 21 S., R. 4 W., Willamette Meridian, Oregon

**CHAINS**

40.365 The center W 1/16 sec. cor. of sec. 17.

---

From the center S 1/16 sec. cor. of sec. 17.

N. 89° 31' 30" W., on the E. and W. center line of the SW $\frac{1}{4}$  of sec. 17.

Descend over SW. slope, through heavy timber and dense undergrowth.

10.55 Gravelled road, 20 lks. wide, bears S. 30° E. and N. 30° W.

18.70 Ward Creek, 15 lks. wide, course S. 15° E.; asc. over NE. slope.

20.025 The SW 1/16 sec. cor. of sec. 17.

Ascend over broken NE. slope.

40.050 The S 1/16 sec. cor. of secs. 17 and 18.

---

Subdivision of Section 31,  
 T. 21 S., R. 4 W., Willamette Meridian, Oregon

---


From the  $\frac{1}{4}$  sec. cor. of secs. 6 and 31, on the S. bdy. of the Tp.

N. 0° 12' 00" W., on the N. and S. center line of sec. 31.

Descend over broken NE. slope, changing to NW. slope, through heavy timber and dense undergrowth.

20.015 Point for the center S 1/16 sec. cor. of sec. 31.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A fir, 11 ins. diam., bears N. 65 $\frac{1}{2}$ ° E., 33 $\frac{1}{2}$  lks. dist., mkd. CS 1/16 S31 BT.

A fir, 8 ins. diam., bears N. 61 $\frac{1}{2}$ ° W., 26 $\frac{1}{2}$  lks. dist., mkd. CS 1/16 S31 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.


Descend over NW. slope.

36.45 South edge of beaver pond, edge bears N. 85° E. and S. 80° W.

37.40 North edge of beaver pond, edge bears NW. and S. 40° E., course NW.; asc. over SW. slope.

40.030 Point for the center  $\frac{1}{4}$  sec. cor. of sec. 31, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.



from which