

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 31,
T. 21 S., R. 4 W., Willamette Meridian, Oregon 18616

CHAINS													
	<p>A fir, 11 ins. diam., bears N. 72° E., 37 lks. dist., mkd. C$\frac{1}{4}$ S 31 BT.</p> <p>A fir, 21 ins. diam., bears S. 86$\frac{1}{2}$° W., 10 lks. dist., mkd. C$\frac{1}{4}$ S31 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over SW. slope.</p>												
52.55	Ridge, bears N. 60° E. and S. 75° W.; desc. over broken NE. slope.												
60.420	<p>The center N 1/16 sec. cor. of sec. 31, established and recorded by Floyd J. Cole, Deputy County Surveyor, in 1914, and is accepted as the corner; determined from the remains of bearing trees mkd. by Cole:</p> <p style="margin-left: 40px;">A decayed fir root crown, size indeterminate, bears N. 88$\frac{1}{2}$° E., 34 lks. dist., with reverse scribe marks BT visible on overgrowth.</p> <p style="margin-left: 40px;">A sawed fir stump, 30 ins. diam., bears S. 88° W., 13 lks. dist., with scribe marks 1/16 visible on opened blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border: none;"> <tr> <td></td> <td style="text-align: center;">C</td> <td></td> </tr> <tr> <td style="text-align: center;">N 1/16</td> <td style="text-align: center;"> </td> <td style="text-align: center;">S 31</td> </tr> <tr> <td></td> <td style="text-align: center;">C</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1988</td> <td></td> </tr> </table> </div> <p>from which new bearing trees</p> <p style="margin-left: 40px;">A fir, 11 ins. diam., bears N. 86 3/4° E., 32 lks. dist., mkd. CN 1/16 S31 BT.</p> <p style="margin-left: 40px;">A fir, 20 ins. diam., bears N. 52$\frac{1}{2}$° W., 27 lks. dist., mkd. CN 1/16 S31 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p style="margin-left: 40px;">N. 0° 10' 30" W., beginning new measurement.</p> <p>Descend over NE. slope.</p>		C		N 1/16		S 31		C			1988	
	C												
N 1/16		S 31											
	C												
	1988												
8.95	Dirt road, 15 lks. wide, bears N. 55° W. and S. 65° E.												
19.660	The $\frac{1}{4}$ sec. cor. of secs. 30 and 31.												
	<hr style="width: 80%; margin: 10px auto;"/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.</p> <p>S. 89° 07' 30" W., on the E. and W. center line of sec. 31.</p> <p>Ascend over broken NE. slope, through heavy timber and dense undergrowth.</p>												
11.25	Dirt road, 15 lks. wide, bears N. 35° E. and S. 20° W.												
18.35	Spur, slopes N. 55° W.; desc. over broken SW. slope.												
33.80	Ravine, drains SW.; asc. over broken SE. slope.												