

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 31,
18617 T. 21 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
36.75	Spur, slopes, S. 10° E., desc. over broken SW. slope.
40.630	The center $\frac{1}{4}$ sec. cor. of sec. 31. Descend over broken SW. slope.
41.95	Creek, 5 lks. wide, course N. 30° W.; asc. over broken NE. slope.
60.470	Point for the center W $\frac{1}{16}$ sec. cor. of sec. 31. Set a stainless steel post, 28 ins. long $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>C W $\frac{1}{16}$ C S 31 1988</p> </div> from which <div style="margin-left: 40px;"> <p>A fir, 9 ins. diam., bears N. 54 $\frac{3}{4}$° E., 24 lks. dist., mkd. CW $\frac{1}{16}$ S31 BT.</p> <p>A fir, 23 ins. diam., bears S. 13$\frac{1}{4}$° W., 28 lks. dist., mkd. CW $\frac{1}{16}$ S31 BT.</p> </div> Deposit white "DEEP-1" magnetic marker at base of stainless steel post. Ascend over broken NE. slope.
65.85	Spur, slopes N. 40° W.; desc. over broken NW. slope.
67.50	Dirt road, 25 lks. wide, bears N. 30° W. and S. 30° E.
72.10	Creek, 5 lks. wide, course N. 35° W.; asc. over broken NE. slope.
79.45	Gravelled road, 25 lks. wide, bears N. 15° W. and S. 15° E.
81.140	The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp. <hr/> From the S $\frac{1}{16}$ sec. cor. of secs. 31 and 32. S. 89° 15' 30" W., on the E. and W. center line of the SE $\frac{1}{4}$ of sec. 31. Ascend over broken NE. slope, through heavy timber and dense undergrowth.
9.20	Dirt road, 15 lks. wide, bears N. 30° W. and S. 30° E., also spur, slopes N. 30° W.; desc. over broken SW. slope.
29.35	Center of beaver pond, 50 lks. wide, drains N. 20° W.; asc. over NE. slope.
40.805	The center S $\frac{1}{16}$ sec. cor. of sec. 31. <hr/> From the W $\frac{1}{16}$ sec. cor. of secs. 6 and 31, on the S. bdy. of the Tp. N. 0° 42' 30" W., on the N. and S. center line of the SW $\frac{1}{4}$ of sec. 31. Descend over NW. slope, through heavy timber and dense undergrowth.
19.980	Point for the SW $\frac{1}{16}$ sec. cor. of sec. 31, at intersection with the E. and W. center line of the SW $\frac{1}{4}$. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.