

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines
18623 T. 22 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A fir, 32 ins. diam., bears N. $1\frac{1}{2}^{\circ}$ E., 91 lks. dist.,
 mkd. $\frac{1}{4}$ S15 BT.

A fir, 10 ins. diam., bears S. 17° E., 90 lks. dist.,
 mkd. $\frac{1}{4}$ S22 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, a point unofficially established as the $\frac{1}{4}$ sec. cor. of secs. 15 and 22 by a Bureau of Land Management administrative survey, date unknown, and is not accepted, bears S. $20^{\circ} 30'$ E., 0.220 chs. dist., monumented with an iron pipe, $\frac{1}{2}$ in. diam., firmly set, projecting 8 ins. above ground.

Descend over NW. slope, changing to SW. slope.

63.75 Creek, 15 lks. wide, course N. 15° W.; asc. over NE. slope.

71.05 Gravelled road, 20 lks. wide, bears N. 70° W. and S. 70° E.

76.800 The cor. of secs. 15, 16, 21, and 22, perpetuated by Wilford N. Haines, Registered Land Surveyor No. 239, date unknown, further perpetuated and recorded by William S. Stoffel, Deputy County Surveyor, in 1964, monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 10 ins. above ground, with washer mkd. WILFORD N HAINES DRAIN OR 239, alongside of which is an iron pipe, $\frac{3}{4}$ in. diam., firmly set, projecting 5 ins. above ground, from which the remains of an original bearing tree:

A burned fir stump, size indeterminate, bears S. 28° E.,
 117 lks. dist., no marks visible. (Record, 118 lks.)

and the remains of a bearing tree mkd. by Stoffel

A root hole, bears N. 84° E., 97 lks. dist., with a down fir stump alongside, size indeterminate, no marks visible.

At the corner point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, directly over the T iron, with brass cap mkd.

T 22 S R 4 W	
S 16	S 15
S 21	S 22
1988	

from which new bearing trees

A fir, 9 ins. diam., bears N. $69\frac{1}{2}^{\circ}$ E., 19 lks. dist.,
 mkd. T22S R4W S15 BT.

A fir, 4 ins. diam., bears S. $25\frac{1}{2}^{\circ}$ E., 31 lks. dist.,
 mkd. X BT.

A fir, 6 ins. diam., bears S. $59\frac{1}{2}^{\circ}$ W., 54 lks. dist.,
 mkd. T22S R4W S21 BT.

A fir, 5 ins. diam., bears N. $81\frac{1}{2}^{\circ}$ W., 44 lks. dist.,
 mkd. X BT.

Deposit white "DEEP-1" magnetic marker at base and iron pipe alongside of stainless steel post.

From this point, the Douglas County Surveyors Office horizontal control station "EVE 1978", bears S. $44^{\circ} 28' 52''$ W., 317.260 chs. dist., monumented with a brass tablet, $3\frac{1}{2}$ ins. diam., concreted in bedrock, with top mkd. DOUGLAS COUNTY SURVEYORS OFFICE EVE 1978.