

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 4 W., Willamette Meridian, Oregon 18624

CHAINS	
	N. 0° 24' 30" W., bet. secs. 15 and 16.
	Descend over NE. slope, through heavy timber and dense undergrowth.
2.20	Gravelled road, 25 lks. wide, bears N. 85° E. and S. 80° W.
6.55	Creek, 15 lks. wide, course N. 55° W.; asc. over SW. slope.
12.65	Gravelled road, 25 lks. wide, bears E. and W.
17.70	Gravelled road, 25 lks. wide, bears N. 70° W. and E.
19.20	Spur, slopes NW.; desc. over NE. slope.
20.075	<p>From this point, a corner established as the S 1/16 sec. cor. of secs. 15 and 16, not recorded, by Wilford N. Haines, Registered Land Surveyor No. 239, in 1972, bears West, 0.025 chs. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 10 ins. above ground, from which bearing trees mkd. by Haines:</p> <p style="margin-left: 40px;">A grand fir, 19 ins. diam., bears S. 17° E. 43 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 28 ins. diam., bears N. 14° W., 41 lks. dist., with healed blaze.</p> <p>This point was not recorded, as far as can be determined it was not recognized as the corner by adjacent landowners, and is not utilized in this survey.</p>
24.75	Gravelled road 25 lks. wide, bears N. 60° E. and N. 80° W.
38.25	Creek, 8 lks. wide, course S. 50° W.; asc. over broken SW. slope.
40.035	<p>Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 22 S R 4 W</p> <p style="margin: 0 0 0 100px;">1/4</p> <p style="margin: 0 0 0 100px;">S 16 S 15</p> <p style="margin: 0 0 0 100px;">1988</p> </div> <p>from which</p> <p style="margin-left: 40px;">A grand fir, 11 ins. diam., bears N. 30 1/4° E., 28 lks. dist., mkd. 1/4 S15 BT.</p> <p style="margin-left: 40px;">A fir, 7 ins. diam., bears N. 56 3/4° W., 25 lks. dist., mkd. 1/4 S16 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a corner unofficially established as the 1/4 sec. cor. of secs. 15 and 16 by a Bureau of Land Management administrative survey, date unknown, and is not accepted, bears S. 53° 08' 00 W., 0.015 chs. dist., monumented with an iron pipe, 1/2 in. diam., firmly set, projecting 12 ins. above ground.</p> <p>From this same point, a corner established as the 1/4 sec. cor. of secs. 15 and 16, not recorded, by Wilford N. Haines, Registered Land Surveyor No. 239, in 1972, bears S. 2° 04' 15" W., 0.168 chs. dist., as determined from the bearing trees mkd. by Haines:</p>