

County Surveyor's Record, Douglas County, Oregon

T. 30 S., R. 6 W., Willamette Meridian, Oregon

18635

CHAINS

The following field notes are those of the subdivision of sections 10 and 15, township 30 south, range 6 west, Willamette Meridian, Oregon

The history of surveys pertaining to this survey is as follows:

The subdivisional lines were surveyed by Addison R. Flint, U. S. Deputy Surveyor, in 1855.

A portion of the subdivisional lines was resurveyed by Lynn M. Roseberry, Cadastral Surveyor, in 1967.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated March 16, 1988, for Group No. 1434, Oregon.

The directions of the lines refer to the true meridian as determined by deflections from azimuths obtained by direct solar observations.

Detectable Electronically Energized particles (DEEP-1 TM) were buried as memorials at certain corner monuments. The "DEEP-1" is composed of strontium encased in a color coded plastic container. The units are 1 inch in diameter, 2½ inches long, weigh 2½ ounces, and are magnetically detectable to an average depth of 8 feet.

Only the true line field notes are given herein. Only those lines bounding public lands were blazed. All lines not forming a closure were measured twice.

The geographic position (NAD 1927) of the NW 1/16 section corner of section 15, as determined from a tie to Oregon State Highway Bench Mark used as Horizontal Control Station "3057" by Douglas County Surveyor's Office, is as follows:

Latitude 42° 58' 01.49" N. Longitude 123° 24' 00.86" W.

The mean magnetic declination is 18° 00' E.

Subdivision of Section 10,
T. 30 S., R. 6 W., Willamette Meridian, Oregon

Beginning at the ¼ sec. of secs. 10 and 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 30 S R 6 W

S 10

¼ S 15

1967

from which bearing trees mkd. by Roseberry

A fir, 37 ins. diam., bears N.80° E., 71 lks. dist., with healed blaze.

A fir, 38 ins. diam., bears S.44° W., 40 lks. dist., with healed blaze.

N. 1° 19' 00" W., on the N. and S. center line of sec. 10.

Ascend over SW. slope, through scattering timber and moderate undergrowth.

27.95 Spur, slopes S. 50° W.; desc. over NW. slope.

39.545 Point for the center ¼ sec. cor. of sec. 10, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins.