

# County Surveyor's Record, Douglas County, Oregon

18637

Subdivision of Section 10,  
T. 30 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">A pine, 40 ins. diam., bears S. 25° W., 164 lks. dist., with scribe mark S visible on opened blaze.</p> <p>and the remains of bearing trees mkd. by Byron</p> <p style="text-align: center;">A pine, 16 ins. diam., bears S. 20° E., 36½ lks. dist., with fragmentary scribe marks visible on partially healed double blaze.</p> <p style="text-align: center;">A root hole, bears N. 26° W., 85 lks. dist., with down pine alongside, size indeterminate, with scribe marks ¼ S10 CS BT visible on open double blaze.</p> <p>and a new bearing tree</p> <p style="text-align: center;">A pine, 10 ins. diam., bears N. 59° W., 46 lks. dist., mkd. ¼ S10 BT.</p> <p>N. 89° 18' 00" W., on the E. and W. center line of sec. 10.</p> <p>Descend over SW. slope, through moderate undergrowth and scattering timber.</p>
2.05	Ravine, drains S. 50° W.; desc. over SW. slope.
12.75	Sanderson Creek, 5 lks. wide, course S. 5° E.; asc. over broken NE. slope.
36.65	Spur, slopes N. 20° W. to saddle; desc. over broken NW. slope.
41.780	The center ¼ sec. cor. of sec. 10.
	Descend over broken NW. slope.
45.15	Creek, 2 lks. wide, course S. 50° W.; asc. over SE. slope.
54.65	Spur, slopes S. 10° W.; desc. over SW slope.
58.90	Creek, 3 lks. wide, course S. 15° E.; asc. over SE. slope.
61.400	Point for the center W 1/16 sec. cor. of sec. 10.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{W } 1/16 \\ \text{C } \text{ S } 10 \text{ C} \\ 1988 \end{array}$
	from which
	<p>A fir, 8 ins. diam., bears S. 26½° E., 34 lks. dist., mkd. X at breast height and BT at the base.</p> <p>A fir, 8 ins. diam., bears N. 10° W., 7 lks. dist., mkd. CW 1/16 S10 BT.</p>
	Deposit white "DEEP-1" magnetic marker at base of stainless steel post.
	Ascend over SE. slope.
72.60	Spur, slopes S. 20° E.; desc. over SW. slope.
81.020	The ¼ sec. cor. of secs. 9 and 10, monumented with an iron post 2½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \text{S } 9 \text{   } \text{S } 10 \\ \text{S } 30 \text{ S } \text{R } 6 \text{ W} \\ 1967 \end{array}$