

County Surveyor's Record, Douglas County, Oregon

18640

Subdivision of Section 15,
T. 30 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

79.780

The $\frac{1}{4}$ sec. cor. of secs. 10 and 15.

From the $\frac{1}{4}$ sec. cor. of secs. 14 and 15, perpetuated and recorded by John H. Markham Jr., Registered Engineer No. 2880, in 1950, from original evidence no longer in existence, monumented with an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above ground, from which the remains of bearing trees mkd. by Markham:

A madrone, 27 ins. diam., bears S. $17\frac{1}{2}^\circ$ E., 80 lks. dist., with healed double blaze.

A fir snag, 20 ins. diam., bears S. 19° W., 3 lks. dist. with scribe marks $\frac{1}{4}$ S15 2880 visible on bark blaze.

At the corner point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 30 S R 6 W
 $\frac{1}{4}$
S 15 | S 14
 1988

from which new bearing trees

A fir, 6 ins. diam., bears N. 23° E., $30\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S14 BT.

A fir, 7 ins. diam., bears N. $73\frac{1}{4}^\circ$ W., 40 lks. dist., mkd. $\frac{1}{4}$ S15 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post and the iron pipe alongside.

N. $89^\circ 02' 00''$ W., on the E. and W. center line of sec. 15.

Ascend over NE. slope, through heavy timber and dense undergrowth.

1.65 Spur, slopes N.; desc. over broken NW. slope.

23.65 Ravine, drains N. 55° E.; asc. over broken SE. slope.

30.90 Dirt road, 20 lks. wide, bears N. 10° E. and S. 10° W.

35.95 Same road, 20 lks. wide, bears N. 30° W. and S.

40.450 The center $\frac{1}{4}$ sec. cor. of sec. 15.

Ascend over SE. slope.

50.50 Ridge, bears NW. and S., to saddle; desc. over NW. slope.

56.30 Ravine, drains S. 30° W.; asc. over SE. slope.

60.925 Point for the center W $1/16$ sec. cor. of sec. 15.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

W $1/16$
C S 15 C
 1988

from which

An oak, 3 ins. diam., bears S. $56\frac{1}{4}^\circ$ W., 35 lks. dist., mkd. X at breast height and BT at the base.

An oak, 8 ins. diam., bears N. 6° W., 29 lks. dist., mkd. CW $1/16$ S15 BT.