

County ^{post} Surveyor's Record, Douglas County, Oregon

18641

Subdivision of Section 15,
T. 30 S., R. 6 W., Willamette Meridian, Oregon

| CHAINS | |
|--------|--|
| | <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over SE. slope.</p> |
| 68.30 | Spur, slopes S. 10° W.; desc. over SW. slope. |
| 75.15 | Creek, 8 lks. wide, course S.; asc. over SE. slope. |
| 80.80 | Spur, slopes S.; desc. over SW. slope. |
| 81.400 | <p>The $\frac{1}{4}$ sec. cor. of secs. 15 and 16, monumented with an iron post, $1\frac{1}{4}$ ins. diam., firmly set, projecting 18 ins. above ground, in a mound of stone 4 ft. base, 1 ft. high, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 30 S $\frac{1}{4}$ S 16 S 15 R 6 W 1963</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A root hole, bears S. 80° E., 188 lks. dist., with down pine alongside, 40 ins. diam., with fragmentary scribe marks visible on opened blaze.</p> <p>and a bearing tree mkd. by Robert M. Thompson, Registered Engineer No. 3683, in 1958</p> <p style="padding-left: 40px;">A cedar, 30 ins. diam., bears N. 42° E., 95$\frac{1}{2}$ lks. dist., with healed double blaze.</p> <p>and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1963</p> <p style="padding-left: 40px;">A cedar, 18 ins. diam., bears N. 89$\frac{1}{4}$° W., 151$\frac{1}{2}$ lks. dist., with healed double blaze.</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 15.</p> <p>N. 1° 21' 00" E., on the N. and S. center line of the NW$\frac{1}{4}$ of sec. 15.</p> <p>Ascend over SE. slope, through scattering timber and moderate undergrowth.</p> |
| 13.15 | Ridge, bears N. 60° W. and S. 60° E., to saddle; desc. over NE. slope. |
| 17.50 | Dirt road, 20 lks. wide, bears N. 30° W. and S. 30° E. |
| 20.055 | <p>Point for the NW 1/16 sec. cor. of sec. 15, at intersection with the E. and W. center line of the NW$\frac{1}{4}$.</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 15 1988 from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 4° E., 51 lks. dist., mkd. NW 1/16 S15 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 27° E., 26 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post</p> |