

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the West Boundary,
T. 30 S., R. 3 W., Willamette Meridian, Oregon 18646

CHAINS

(Restoring the survey by Nathaniel Ford, in 1855, the retracement by Dennis Hathorn, in 1857, the resurvey by William Thiel, in 1889, the resurvey by William M. Bushey, in 1893, and the resurvey by Wayne L. Rogers, Lance J. Bishop, and James L. White, in 1983-84)

Beginning at the $\frac{1}{4}$ sec. cor. of sec. 19 only, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 30 S
R 4 W | R 3 W
 | $\frac{1}{4}$
 | S 19
 1983

from which the remains of bearing trees mkd. by Rogers, Bishop, and White

An Oak, 44 ins. diam., bears N. 6° E., 467 lks. dist., with scribe marks $\frac{1}{4}$ S19 BT visible on open blaze.

An Oak snag, 21 ins. diam., bears S. $54\frac{1}{2}^\circ$ E., $7\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ S19 BT visible on open blaze.

No other suitable trees available.

N. $2^\circ 54' 00''$ E., on the W. bdy. of sec. 19.

Descend over NW. slope, through pastureland.

- 1.40 Wood fence, bears N. 70° E. and S. 70° W.
- 1.60 Gravelled driveway, 15 lks. wide, bears N. 70° E. and S. 70° W.
- 10.00 Dirt road, 15 lks. wide, bears N. 40° E. and S. 40° W.
- 11.00 Bland Branch, 5 lks. wide, course S. 75° W.; asc. over SE. slope, also enter Bland Mountain Fire area.
- 11.85 From this point, a point established as the closing cor. of secs. 13 and 14, T. 30 S., R. 4 W., and recorded by George J. Wenderoth, Registered Land Surveyor No. 5, in 1950, bears East, 0.71 chs. dist., monumented with an axle, $1\frac{1}{4}$ ins. diam., firmly set flush with ground, from which a bearing tree mkd. by Wenderoth:
 - An oak, 14 ins. diam., bears S. 47° W., 25 lks. dist., with healed blaze.
- 12.870 True point for the closing cor. of secs. 13 and 24, T. 30 S., R. 4 W., hereinafter described.
 - Ascend over broken SE. slope.
- 22.30 Spur, slopes S. 70° E.; desc. over NE. slope.
- 28.50 Creek, 2 lks. wide, course S. 60° E.; asc. over SE. slope.
- 32.380 Point for the S $\frac{1}{16}$ sec. cor. of sec. 13 only, T. 30 S., R. 4 W., at midpoint latitudinally between the closing cor. of secs. 13 and 24 and the $\frac{1}{4}$ sec. cor. of sec. 13 only, on the E. bdy. of the section.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S $\frac{1}{16}$ |
S 13 |
 1988

from which

An oak, 6 ins. diam, bears N. 54° E., 48 lks. dist.,