

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the West Boundary,
18647 T. 30 S., R. 3 W., Willamette Meridian, Oregon

| CHAINS | | | | | | | | | | | |
|--------|--|--------|--|-------|-------|---|--|------|--|------|--|
| | <p style="text-align: center;">mkd. X at breast height, BT at the base.</p> <p style="text-align: center;">An oak, 8 ins. diam., bears S. 8° W., 37 lks. dist., mkd. S 1/16 S13 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Ascend over SE. slope.</p> | | | | | | | | | | |
| 38.830 | <p>The cor. of secs. 18 and 19 only, monumented with the original corner tree, a madrone, 17 ins. diam., with healed blaze, from which the remains of bearing trees mkd. by Thiel:</p> <p style="padding-left: 40px;">A madrone, 16 ins. diam., bears S. 18° W., 8 lks. dist., with burned blaze.</p> <p style="padding-left: 40px;">A burned fir snag, 34 ins. diam., bears N. 18° W., 35 lks. dist., with burned blaze.</p> <p>and the remains of a bearing tree mkd. by George J. Wenderoth, Registered Land Surveyor No. 5, in 1950</p> <p style="padding-left: 40px;">A burned fir snag, 20 ins. diam., bears N. 15½° E., 104 lks. dist., with healed blaze.</p> <p>and a reference monument and remains of a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1963</p> <p style="padding-left: 40px;">An iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, bears North, 0.015 chs. dist., with brass cap mkd. COUNTY SURVEYORS OFFICE T30S R3W S18 S19 1963.</p> <p style="padding-left: 40px;">A burned fir snag, 15 ins. diam., bears S. 89½° E., 44 lks. dist., with healed blaze.</p> <p>Land, rolling hills. Soil, rocky clay. Timber, pine, yew, oak, fir, cedar, maple, madrone, alder, and ash; undergrowth, salal, Oregon grape, poison oak, salmonberry, blackberry, huckleberry, hazel, arrowwood, ferns, and young timber.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>N. 2° 02' 00" E., on the W. bdy. of sec. 18.</p> <p>Ascend over SE. slope, through heavy burned timber.</p> | | | | | | | | | | |
| 4.55 | <p>Top of ascent, slopes E.; desc. over NE. slope.</p> | | | | | | | | | | |
| 10.45 | <p>Bland Branch, 5 lks. wide, course S. 50° E.; asc. broken SW. slope, also leave Bland Mountain Fire area.</p> | | | | | | | | | | |
| 13.050 | <p>Point for the ¼ sec. cor. of sec. 13 only, T. 30 S., R. 4 W., at proportionate distance latitudinally on the E. bdy. of the section.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="padding: 0 10px;">T 30 S</td></tr> <tr><td style="padding: 0 5px;">R 4 W</td><td style="border-left: 1px solid black; padding: 0 5px;">R 3 W</td></tr> <tr><td colspan="2" style="text-align: center; padding: 0 10px;">¼</td></tr> <tr><td colspan="2" style="text-align: center; padding: 0 10px;">S 13</td></tr> <tr><td colspan="2" style="text-align: center; padding: 0 10px;">1988</td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A maple, 19 ins. diam., bears N. 61° W., 44 lks. dist., mkd. ¼ S13 BT.</p> <p style="padding-left: 40px;">A madrone, 22 ins. diam., bears N. 41° W., 106 lks. dist., mkd. ¼ S13 BT.</p> | T 30 S | | R 4 W | R 3 W | ¼ | | S 13 | | 1988 | |
| T 30 S | | | | | | | | | | | |
| R 4 W | R 3 W | | | | | | | | | | |
| ¼ | | | | | | | | | | | |
| S 13 | | | | | | | | | | | |
| 1988 | | | | | | | | | | | |