

County Surveyor's Record, Douglas County, Oregon 5

Dependent Resurvey of a Portion of the West Boundary,
T. 30 S., R. 3 W., Willamette Meridian, Oregon 18648

CHAINS									
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.								
	Ascend over broken SW. slope, changing to SE. slope.								
32.25	Top of rock bluff, 15 ft. high, edge bears E. and W.								
32.360	Point for the former $\frac{1}{4}$ sec. cor. of secs. 13 and 18, established by Nathaniel Ford in 1854, which is now an Angle Point, determined by the method of irregular boundaries, based on the Thiel resurvey; there is no remaining evidence of the original corner.								
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.								
	<table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 10px;">AP</td></tr> <tr><td style="padding: 0 10px;">T 30 S</td></tr> <tr><td style="padding: 0 10px;">R 4 W R 3 W</td></tr> <tr><td style="padding: 0 10px;">S 13 S 18</td></tr> <tr><td style="padding: 0 10px;">1988</td></tr> </table>	AP	T 30 S	R 4 W R 3 W	S 13 S 18	1988			
AP									
T 30 S									
R 4 W R 3 W									
S 13 S 18									
1988									
	from which								
	An oak, 6 ins. diam., bears N. 49° E., 26 lks. dist., mkd. AP S18 BT.								
	A fir, 30 ins. diam., bears N. 31° W., 46 lks. dist., mkd. AP S13 BT.								
	N. 0° 16' 00" E., beginning new measurement.								
	Ascend over broken SE. slope, changing to broken SW. slope.								
18.000	True point for the closing cor. of secs. 12 and 13, T. 30 S., R. 4 W., hereinafter described.								
	Ascend over SW. slope.								
22.95	Ridge, bears N. 70° W. and S. 70° E.; desc. over steep NE. slope.								
38.550	The Angle Point bet. secs. 12 and 18, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.								
	<table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 10px;">T 30 S</td><td style="padding: 0 10px;">T 30 S</td></tr> <tr><td style="padding: 0 10px;">S 12</td><td style="padding: 0 10px;">S 19</td></tr> <tr><td style="padding: 0 10px;">R 4 W</td><td style="padding: 0 10px;">R 3 W</td></tr> <tr><td style="padding: 0 10px;">1965</td><td></td></tr> </table>	T 30 S	T 30 S	S 12	S 19	R 4 W	R 3 W	1965	
T 30 S	T 30 S								
S 12	S 19								
R 4 W	R 3 W								
1965									
	from which the bearing trees mkd. by Jelley, in 1965								
	A fir, 14 ins. diam., bears S. 17° E., 13 lks. dist., with healed blaze.								
	A fir, 12 ins. diam., bears S. 38° W., $21\frac{1}{2}$ lks. dist., with healed blaze.								
	From this point, the United States Geological Survey triangulation station "BLAND MTN," bears S. 13° 00' 00" E., 17.365 chs. dist., monumented with a brass tablet, $3\frac{1}{2}$ ins. diam., cemented in bedrock $1\frac{1}{2}$ x 1 ft., 6 ins. high, mkd. U S GEOLOGICAL SURVEY BLAND MTN 1953 BENCH MARK.								
	Land, mountainous. Soil, rocky clay. Timber, fir, cedar, maple, alder, willow, chinquapin, madrone, ash, and pine; undergrowth, hazel, salal, Oregon grape, poison oak, ferns, arrowwood, manzanita, salmonberry, huckleberry, and young timber.								