

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
 18651 T. 30 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Ascend over SE. slope.

24.40 Spur, slopes S. 5° W.; asc. over SW. slope.

38.640 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14, determined by the method of irregular boundaries; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 30 S R 4 W
 $\frac{1}{4}$
 S 14 | S 13
 1988

from which

A fir, 10 ins. diam., bears S. 47° E., 57 lks. dist.,
 mkd. $\frac{1}{4}$ S13 BT.

A fir, 9 ins. diam., bears N. 11° W., 63 lks. dist.,
 mkd. $\frac{1}{4}$ S14 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

 N. 0° 14' 00" W., beginning new measurement.

10.70 Spur, slopes S. 60° W.; desc. over NW. slope.

18.490 Point for the N 1/16 sec. cor. of secs. 13 and 14.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

N 1/16
 S 14 | S 13
 1988

from which

A fir, 25 ins. diam., bears N. 29° E., 20 lks. dist.,
 mkd. N 1/16 S13 BT.

A fir, 19 ins. diam., bears N. 13½° W., 70 lks. dist.,
 mkd. N 1/16 S14 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Descend over NW. slope.

24.05 Creek, 1 lks. wide, course S. 35° W.; asc. over SW. slope.

35.70 Ridge, bears N. 80° E. and S. 80° W., to saddle; desc. over NW. slope.

36.980 The cor. of secs. 11, 12, 13, and 14, monumented with the basalt stone, 24 x 11 x 6 ins. loosely set by Thiel, projecting 16 ins. above ground, with 3 notches on S. edge and 1 notch on E. edge, with top corner chipped off, from which the remains of an original bearing tree:

A root hole, bears N. 53° W., 35 lks. dist., with decayed fir alongside, size indeterminate, with scribe marks OS visible on decayed blaze.

At the corner point