

County Surveyor's Record, Douglas County, Oregon.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

18652

CHAINS

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 30 S R 4 W			
S 11	S 12		
S 14	S 13		
1988			

from which new bearing trees

A fir, 14 ins. diam., bears N. 25¼° E., 26 lks. dist.,
mkd. T30S R4W S12 BT.

A fir, 8 ins. diam., bears S. 31¼° E., 15 lks. dist.,
mkd. T30S R4W S13 BT.

A fir, 15 ins. diam., bears S. 53¾° W., 44 lks. dist.,
mkd. T30S R4W S14 BT.

A fir, 15 ins. diam., bears N. 81¼° W., 58 lks. dist.,
mkd. T30S R4W S11 BT.

Deposit a white "DEEP-1" magnetic marker at the base and the marked stone alongside the stainless steel post.

Land, mountainous.

Soil, rocky clay.

Timber, maple, fir, chinquapin, cedar, ash, madrone, dogwood, cherry, oak, and pine; undergrowth, poison oak, vine maple, arrowwood, hazel, blackberry, huckleberry, salmonberry, ferns Oregon grape, salal, and young timber.

N. 88° 59' 00" E., bet. secs. 12 and 13.

Ascend over NW slope, through heavy timber and dense undergrowth.

5.15 Ridge, bears N. 75° E. and S. 75° W., to saddle; asc. over SW. slope.

9.05 Spur, slopes S.; desc. over SE. slope.

34.95 Head of ravine, drains S. 15° E.; asc. over SW. slope.

39.465 The original closing cor. of secs. 12 and 13, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1958, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S			
R S 12	S 18 R		
4 S 13	3		
W CC			
1958			

from which a bearing tree and bearing object mkd. by Byron

An oak, 12 ins. diam., bears S. 40° W., 278 lks. dist.,
with fragmentary scribe marks visible on partially
healed double blaze.

The chisel mark X on the face of a rock outcrop, 3 ft.
high, 3 ft. wide, bears N. 37¾° W., 34½ lks. dist.

This corner now becomes an amended corner.

Ascend over SW. slope.