

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
18657 T. 25 S., R. 1 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 25 S

S 11	S 12	✓
S 14	S 13	

R 1 W
1966

from which the remains of original bearing trees

A sawed fir stump, 18 ins. diam., bears N. 88° E.,
31 lks. dist., no marks visible.

A root hole, bears N. 38½° W., 27 lks. dist., with down
fir alongside, 18 ins. diam., with scribe marks T25S
R1W S11 visible on opened blaze.

and the remains of bearing trees mkd. by Lecklider

A root hole, bears S. 60° W., 51 lks. dist., with down
fir alongside, 34 ins. diam., with scribe marks 4079
visible on open double blaze.

A fir, 35 ins. diam., bears N. 8° W., 66 lks. dist., with
scribe marks S11 RE 4079 BT visible on partially
healed double blaze.

and the remains of bearing trees mkd. by Tracy

A root hole, bears S. 20° W., 60 lks. dist., with down
cedar alongside, 12 ins. diam., with scribe marks
T25S R1W S14 CS BT visible on open double blaze.

A cedar, 25 ins. diam., bears N. 41° W., 76 lks. dist.,
with fragmentary scribe marks visible on partially
healed double blaze.

and new bearing trees

A fir, 4 ins. diam., bears N. 45° E., 19 lks. dist.,
mkd. X BT.

A madrone, 12 ins. diam., bears S. 46½° E., 34 lks. dist.,
mkd. T25S R1W S13 BT on the bark.

A fir, 15 ins. diam., bears S. 60° W., 63 lks. dist.,
mkd. T25S R1W S14 BT.

S. 89° 41' 00" W., bet. secs. 11 and 14.

Descend over SW. slope, changing to NW. slope, through heavy
timber and dense undergrowth.

18.85 Gravelled road, 20 lks. wide, bears N. 5° E., and S. 5° W.

20.150 Point for the E 1/16 sec. cor. of secs. 11 and 14.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

E 1/16 S 11
S 14
1988

from which

A fir, 5 ins. diam., bears S. 63½° E., 12½ lks. dist.,
mkd. E 1/16 S14 BT.