

# County Surveyor's Record, Douglas County, Oregon

18659 Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 25 S., R. 1 W., Willamette Meridian, Oregon

## CHAINS

A cedar, 18 ins. diam., bears S.  $28\frac{1}{2}^{\circ}$  E., 61 lks. dist.,  
with fragmentary scribe marks visible on partially  
healed double blaze.

A cedar snag, 17 ins. diam., bears South, 35 lks. dist.,  
with scribe marks T25S R1W S15 BT visible on open  
double blaze.

and the remains of a bearing tree mkd. by Tracy

A sawed cedar stump, 12 ins. diam., bears N.  $11\frac{1}{2}^{\circ}$  W.,  
92 lks. dist., with scribe marks T25S R1W S10 visible  
on open blaze.

and new bearing trees

A fir, 4 ins. diam., bears S.  $72^{\circ}$  W., 23 lks. dist.,  
mkd. X BT.

A fir, 6 ins. diam., bear N.  $67\frac{1}{2}^{\circ}$  W., 40 lks. dist.,  
mkd. T25S R1W S10 BT.

From this point, a control point at latitude  $43^{\circ} 25' 21.81''$  N.  
and longitude  $122^{\circ} 47' 01.66''$  W., established in conjunction with  
the survey for Group 1347, bears N.  $7^{\circ} 58' 54''$  W., 83.040 chs.  
dist., monumented with a finned aluminum rod, 36 ins. long,  $\frac{1}{4}$  in.  
diam., firmly set 36 ins. in the ground, in a collar of concrete,  
with aluminum cap mkd. EC1 G 1347 1987.

---

Subdivision of Section 14,  
T. 25 S., R. 1 W., Willamette Meridian, Oregon

---

From the  $\frac{1}{4}$  sec. cor. of secs. 14 and 23, perpetuated and recorded  
by Vernon R. Tracy, Deputy County Surveyor, in 1966, determined  
at record bearing and distance from the remains of an original  
bearing tree:

An alder snag, 19 ins. diam., bears N.  $72^{\circ}$  W., 8 lks.  
dist., with scribe mark 4 visible on bark blaze.

and the remains of bearing trees mkd. by Tracy

A hemlock, 14 ins. diam., bears S.  $76^{\circ}$  E., 21 lks. dist.,  
with healed double blaze.

A fir snag, 20 ins. diam., bears N.  $10^{\circ}$  W., 79 lks. dist.,  
with healed double blaze.

At the corner point

Drive an aluminum drive rod,  $\frac{1}{4}$  in. diam., 52 ins. long, 48 ins. in  
the ground, with aluminum cap mkd.

T 25 S R 1 W  
 $\frac{1}{4}$  S 14  
S 23 ✓  
1988

from which a new bearing tree

An alder, 5 ins. diam., bears N.  $9^{\circ}$  E., 31 lks. dist.,  
mkd.  $\frac{1}{4}$  S14 BT on the bark.

The corner is located in a swamp.

N.  $0^{\circ} 13' 30''$  E., on the N. and S. center line of sec. 14.

0.25 Leave swamp, edge bears E. and W.