

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 14,
T. 25 S., R. 1 W., Willamette Meridian, Oregon

18660

CHAINS	
4.95	Canton Creek, 50 lks. wide, course S. 50° E.; asc. over SW. slope.
8.75	Canton Creek Road, oiled, 30 lks. wide, bears N. 10° W. and S. 10° E.
12.50	Top of ascent, slopes N. 70° W.; desc. over NW. slope.
16.35	Canton Creek Road, oiled, 30 lks. wide, bears N. 15° E. and S. 10° W.
20.45	Canton Creek, 50 lks. wide, course SW.; asc. over creek bottom.
22.80	Camp Creek, 3 lks. wide, course S. 50° E.; asc. over broken SW. slope.
34.00	Spur, slopes S. 30° E.; desc. over broken NE. slope.
39.785	Point for the center $\frac{1}{4}$ sec. cor. of sec. 14, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 25 S R 1 W C $\frac{1}{4}$ S 14 1988
	from which
	A fir, 5 ins. diam., bears N. 49° E., 25 lks. dist., mkd. C $\frac{1}{4}$ S14 BT.
	A fir, 4 ins. diam., bears S. 57° E., 22 lks. dist., mkd. X BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	Descend over NE. slope.
43.45	Creek, 5 lks. wide, course E.; asc. over SE. slope.
47.80	Top of ascent, slopes SE.; desc. NE. slope.
55.35	Canton Creek, 50 lks. wide, course SE.; continue over creek bottom.
60.000	Point for the center N $\frac{1}{16}$ sec. cor. of sec. 14.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	C N $\frac{1}{16}$ S 14 C 1988
	from which
	A fir, 5 ins. diam., bears N. 50° E., 92 lks. dist., mkd. X BT.
	A fir, 14 ins. diam., bears N. $87\frac{1}{2}$ ° W., 69 lks. dist., mkd. CN $\frac{1}{16}$ S14 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	Continue over creek bottom.