

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 14,  
**18661** T. 25 S., R. 1 W., Willamette Meridian, Oregon

<p>CHAINS</p> <p>75.25</p> <p>80.215</p>	<p>Canton Creek, 50 lks. wide, course S.50°W.; asc. over SE slope.</p> <p>Spur, slopes NE.; desc. over NE. slope.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 14.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 14.</p> <p>S. 89° 43' 00" W., on the E. and W. center line of sec. 14.</p> <p>Descend over broken SW. slope, through heavy young timber and dense undergrowth.</p> <p>8.30 Creek, 1 lk. wide, course N. 70° W.; desc. over W. slope.</p> <p>9.30 Creek, 1 lk. wide, course S. 75° W.; desc. over broken SW. slope.</p> <p>12.50 Gravelled road, 20 lks. wide, bears N. and S.</p> <p>20.110 Point for the center E 1/16 sec. cor. of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 15 ins. in the ground over X marked in bedrock, supported in mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>C E 1/16 C</p> <p>S 14</p> <p>1988</p> </div> <p>from which</p> <div style="margin-left: 40px; margin-bottom: 10px;"> <p>A fir, 5 ins. diam., bears S. 4<math>\frac{1}{2}</math>° E., 29 lks. dist., mkd. E 1/16 S14 BT.</p> </div> <div style="margin-left: 40px; margin-bottom: 10px;"> <p>A maple, 5 ins. diam., bears N.23° W., 17<math>\frac{1}{2}</math> lks. dist., mkd. E 1/16 S14 BT.</p> </div> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over SW. slope.</p> <p>21.05 Creek, 1 lk. wide, course N. 80° W.; asc. over NE. slope.</p> <p>24.85 Spur, slopes NW.; desc. over SW. slope.</p> <p>30.25 Canton Creek Road, oiled, 30 lks. wide, bears N. 10° W. and S. 10° E.</p> <p>31.80 Canton Creek, 50 lks. wide, course S. 15° E.; asc. over NE. slope.</p> <p>40.220 The center <math>\frac{1}{4}</math> sec. cor. of sec. 14.</p> <p>Ascend over NE. slope.</p> <p>55.40 Spur, slopes S. 50° E.; desc. over SW. slope.</p> <p>63.95 Camp Creek, 15 lks. wide, course SE.; asc. over NE. slope.</p> <p>64.90 Spur, slopes N. 5° E.; desc. over NW. slope.</p> <p>66.35 Camp Creek, 15 lks. wide, course N. 60° E.; asc. over SE. slope.</p> <p>81.10 Gravelled road, 20 lks. wide, bears N. 50° E. and S. 50° W.</p> <p>81.515 The <math>\frac{1}{4}</math> sec. cor. of secs. 14 and 15, monumented with an iron post, 1<math>\frac{1}{2}</math> ins. diam., loosely set, projecting 10 ins. above ground, with brass cap mkd.</p>
--	---