

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 14,
T. 25 S., R. 1 W., Willamette Meridian, Oregon 18662

CHAINS

T 25 S R 1 W

¼

S 15 | S 14

1988

1978 *

*+ Per research
12/29/2005 JC
D.C.S.D.*

from which the remains of the original bearing trees

A cedar, 26 ins. diam., bears N. 46° E., 22 lks. dist.,
with fragmentary scribe marks visible on opened blaze.

A sawed hemlock stump, size indeterminate, bears
S. 68° W., 21 lks. dist., no marks visible.

and a bearing tree mkd. by Jelley

A pine, 7 ins. diam., bears N. 59½° W., 26 lks. dist.,
with healed blaze.

Reset the iron post 24 ins. in the ground.

From this point, the witness corner established by Milo E. Godfrey, Deputy County Surveyor, in 1962, bears North, 0.170 chs. dist., monumented with an iron post, 1¼ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T25S R1W S15 S14 10 FT S to ¼ COR 1962, from which the remains of a bearing tree mkd. by Godfrey:

A hemlock snag, 9 ins. diam., bears N. 66° W.,
24 lks. dist., with fragmentary scribe marks
visible on partially healed double blaze.

The corner is located on the W. edge of road, in cutbank.

From the center E 1/16 sec. cor. of sec. 14.

N. 0° 15' 30" E., on the N. and S. center line of the NE¼ of sec. 14.

Ascend over SW. slope, through heavy timber and dense undergrowth.

- 2.50 Spur, slopes W.; desc. over NW. slope.
 - 7.20 Creek, 5 lks. wide, course S. 55° W.; asc. over SW. slope.
 - 10.20 Spur, slopes N. 60° W.; desc. over NW. slope.
 - 11.85 Gravelled road, 15 lks. wide, bears N. 35° E. and S. 85° W., in a curve.
 - 12.50 Bottom of descent, drains W.; asc. over SW. slope.
 - 17.50 Gravelled road, 15 lks. wide, bears N. 55° W. and S. 55° E.
 - 18.85 Creek, 2 lks. wide, course S. 85° W.; asc. over SW. slope.
 - 20.225 Point for the NE 1/16 sec. cor. of sec. 14, at intersection with the E. and W. center line of the NE¼ of sec. 14.
- Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

NE 1/16
S 14
1988

from which

A fir, 6 ins. diam., bears S. 10° E., 33 lks. dist.,
mkd. NE 1/16 S14 BT.