

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 4 W., Willamette Meridian, Oregon

18666

**CHAINS**

(Restoring the survey by Harvey Gordon and Charles T. Gardner,  
in 1855)

Beginning at the cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground (with a 1 in. "T" shaped iron rod, firmly set alongside, projecting 15 ins. above ground), with brass cap mkd.

T 24 S R 4 W			
S 3	S 2		
S 10	S 11		
1957			

from which the remains of an original bearing tree

A burned cedar stump, size indeterminate, bears  
S.46° W., 48 lks. dist., no marks visible.

and the remains of a bearing tree mkd. by Wilford N. Haines,  
Registered Land Surveyor No. 239, in 1957

A sawed fir stump, 24 ins. diam., bears S. 82° E., 349 lks.  
dist., no marks visible. (Record, 374 lks.)

and the remains of bearing trees mkd. by Roseberry

A root hole, bears N. 65° E., 346 lks. dist., with a down  
fir lying alongside, 25 ins. diam., with healed blaze.

A fir, 23 ins. diam., bears S. 10½° E., 311 lks dist., with  
healed blaze. (Record 308 lks.)

A fir, 26 ins. diam., bears S. 64½° W., 282 lks. dist., with  
healed blaze. (Record, 284 lks.)

and new bearing trees

A fir, 15 ins. diam., bears N. 80° E., 23 lks. dist., mkd.  
T24S R4W S2 BT.

A fir, 12 ins. diam., bears N. 65° W., 24 lks. dist., mkd.  
T24S R4W S3 BT.

North, bet. secs. 2 and 3, marking and blazing the true line.

Ascend over SW. slope, through heavy timber and dense undergrowth.

7.75 Spur, slopes S. 80° W.; desc. over NW. slope.

12.15 Creek, 1 lk. wide, course W.; asc. over S. slope.

14.35 Spur, slopes S. 80° W.; desc. over NW. slope.

24.90 Creek, 4 lks. wide, course S. 55° W.; asc. over SW. slope.

28.95 Gravel road, 20 lks. wide, bears N. 80° E. and S. 80° W.

29.40 Spur, slopes W.; desc. over NW. slope.

34.55 Creek, 3 lks. wide, course N. 65° W.; asc. over SW. slope.

39.260 Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate  
distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in  
the ground, with brass cap mkd.