

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the West Boundary,
18673 T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A decayed oak snag, 25 ins. diam., bears S. 86° W.,
319 lks. dist., no marks visible.

and the remains of bearing trees mkd. by James W. Byron, Deputy
County Surveyor, in 1962, as recorded in Douglas County Surveyors
Office Corner Renewal File, T. 29 S., R. 8 W., No. 117.

An ash stump, 10 ins. dia., bears N. 3¾° E., 66 lks.
dist., with healed double blaze.

An oak, 7 ins. diam., bears N. 23¾° W., 69 lks. dist.,
with healed double blaze.

and new bearing trees

A fir, 5 ins. diam., bears N. 66¾° E., 6 lks. dist.,
mkd. T29S R8W S30 BT.

A fir, 6 ins. diam., bears S. 40¾° E., 250 lks. dist.,
mkd. T29S R8W S31 BT.

A pine, 10 ins. diam., bears S. 65¼° W., 87 lks. dist.,
mkd. T29S R9W S36 BT.

The corner is located at base of dike of old log pond.

From this point, the National Geodetic Survey Oregon Primary GPS
Station WCAM 1989, at latitude 43° 00' 37.495 N., Longitude
123° 41' 54.342" W. (NAD 1927), bears S. 68° 41' 34" E., 11.395
chs. dist., monumented with a brass tablet, 3½ ins. diam., set in
concrete, 24 ins. below the surface of the ground on the north
shoulder of State Highway No. 42, with top mkd. NGS Oregon Primary
GPS Station WCAM 1989.

Dependent Resurvey of the East and West Center Line
of the Northwest One-Quarter of Section 31,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the survey by Donald R. Beck, Cadastral Surveyor,
in 1965)

From the center N 1/16 sec. cor. of sec. 31, reset, perpetuated
and recorded by Roderick B. Kimberling, Deputy County Surveyor, in
1977, as recorded in Douglas County Surveyors Office Corner Renewal
File, T. 29 S., R. 8 W., No. 173; monumented with an iron post, 2½
ins. diam., firmly set, projecting 4 ins. above ground, with brass
cap mkd.

T 29 S R 8 W
C
N 1/16 | S 31
C
RESET 1977
1965

from which the remains of bearing trees mkd. by Beck

An oak, 13 ins. diam., bears N. 30° E., 39 lks. dist.,
with healed blaze.

A fir snag, 16 ins. diam., bears S. 75¾° W., 42½ lks.
dist., with fragmentary scribe marks visible on
partially healed blaze.

and a bearing tree mkd. by Kimberling