

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the East and West Center Line
of the Northwest One-Quarter of Section 31,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

18674

CHAINS	
	<p style="text-align: center;">A cedar, 13 ins. diam., bears S. 6° E., 35 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p>
	<p>S. 89° 22' 30" W., on the E. and W. center line of the NW¼ of sec. 31.</p>
	<p>Descend over NW. slope, through heavy timber and dense undergrowth.</p>
5.70	<p>Enter swamp, edge bears N. 40° E. and S. 40° W.; continue over swamp.</p>
11.30	<p>Leave swamp, edge bears N. 20° W. and S. 20° E.; asc. over NE slope.</p>
12.45	<p>Woven wire fence, extends N. and S.</p>
13.75	<p>Spur, slopes N. 10° W.; desc. over broken NW. slope.</p>
25.70	<p>Woven wire fence, extends N. 50° W. and S. 50° E.</p>
32.95	<p>Dir road, 15 lks. wide, bears N. and S.</p>
33.80	<p>From this point, a fence corner bears N., 0.050 chs. dist., with woven wire fence extending N. and W.</p>
36.05	<p>Woven wire fence, extends E. and W.</p>
40.46	<p>From this point, a fence corner bears S., 0.050 chs. dist., with woven wire fence extending N. and E.</p>
40.860	<p>Point for Corner No. 1, Lot 8, sec. 31.</p> <p style="text-align: center;">Set a brass tablet, 3½ ins. diam., 3¼ in. stem, cemented in drill hole in bedrock, 7 ins. below ground level, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>from which</p> <p style="text-align: center;">A grand fir, 18 ins. diam., bears S. 80° E., 64 lks. dist., mkd. COR S31 BT.</p> <p>Descend over NW. slope.</p>
41.05	<p>Intersect the E. side of a wood frame shed, 22 x 13 ft., at a point from which the SE. cor. bears S. 20° E., 0.07 chs. dist., the long side bears N. 20° W. and S. 20° E.</p>
41.40	<p>Intersect the E. side of an "L" shaped wood frame house, the east wing 50 x 12 ft., at a point from which the SE. cor. bears S. 20° E., 0.013 chs. dist., the long side bears N. 20° W. and S. 20° E.</p>
41.860	<p>Point for Corner No. 2, Lot 8, sec. 31.</p> <p style="text-align: center;">Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>from which</p>