

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 4 W., Willamette Meridian, Oregon

18679

CHAINS	
	<p>above ground, with brass cap mkd.</p> <p style="text-align: center;">T 28 S R 4 W S 15 S 14 S 22 S 23 1965</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A rotted madrone stump, 18 ins. diam., bears N. 76° E., 49 lks. dist., no marks visible. (Record, N. 77° E., 47 lks.)</p> <p>and the remains of bearing trees mkd. by Jelley</p> <p style="padding-left: 40px;">A chinquapin, 14 ins. diam., bears N. 44½° E., 56 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A madrone stump, 14 ins. diam., bears S. 42° E., 33 lks. dist., with scribe marks T28S R4W S23 BT visible on a partially healed blaze. (Record, S. 45½° E.)</p> <p style="padding-left: 40px;">A fir stump, 9 ins. diam., bears S. 13° W., 72 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A cedar, 13 ins. diam., bears N. 55° W., 69 lks. dist., with healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 10½° E., 13 lks. dist., mkd. T28S R4W S23 BT.</p> <p style="padding-left: 40px;">A fir, 3 ins. diam., bears S. 65° W., 16 lks. dist., mkd. X BT.</p> <p>From this point, a BLM control point No. EC71004 "LEE CREEK," at latitude 43° 07' 40.94" N. and longitude 123° 08' 54.04" W., established in conjunction with this survey, bears N. 34° 17' 00" W., 6.564 chs. dist., monumented with a finned aluminum rod, 36 ins. long, ¼ in. diam., set 36 ins. in the ground, in a collar of concrete, with aluminum cap mkd. EC 1 G 1398 1987.</p> <p>N. 0° 19' 00" W., bet. secs. 14 and 15.</p> <p>Ascend over SE. slope, through scattering timber and dense undergrowth.</p> <p>6.50 Dirt road, 15 lks. wide, on ridge, bearing N. 65° E. and S. 65° W.; desc. over broken NW. slope.</p> <p>11.70 Ravine, drains N. 50° W.; asc. over SW. slope.</p> <p>13.20 Spur, slopes W.; desc. over broken NW. slope.</p> <p>26.730 Intersect line 2-3 of the Morning Star Placer, Mineral Survey No. 979, and point for the crossing closing corner, which has been established by person(s) unknown, and monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above ground.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 28 S R 4 W MS 979 S 15 S 14 CCC 1991</p>