

County Surveyor's Record, Douglas County, Oregon

18680

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

from which

A cedar, 14 ins. diam., bears S. $11\frac{1}{2}^{\circ}$ E., 40 $\frac{1}{2}$ lks.
dist., mkd. T28S R4W S14 CCC BT.

A fir, 26 ins. diam., bears S. $31\frac{1}{4}^{\circ}$ W., 58 lks.
dist., mkd. T28S R4W S15 CCC BT.

Deposit white "DEEP-1" magnetic marker at base and iron rod
alongside the stainless steel post.

From this point, Cor. No. 2 of the Morning Star Place, Mineral
Survey No. 979, bears N. $62^{\circ} 54' 00''$ E., 4.270 chs. dist.,
hereinafter described.

Continue to desc. over broken NW. slope.

32.10 Graveled road, 20 lks. wide, bears N. 70° E. and S. 70° W.

33.50 Graveled road, 15 lks. wide, bears N. 60° E. and S. 60° W.

36.150 Point for a crossing closing corner at the intersection with line
1-2 of the Morning Star Placer, Mineral Survey No. 979, Oregon.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 25 ins.
in the ground, with brass cap mkd.

T 28 S R 4 W
CCC
S 15 | S 14

MS 979
1991

from which

A yew, 14 ins. diam., bears N. $37\frac{1}{2}^{\circ}$ E., 52 lks. dist.,
mkd. T28S R4W S14 CCC BT.

A yew, 10 ins. diam., bears N. $27\frac{1}{4}^{\circ}$ W., 37 $\frac{1}{2}$ lks. dist.,
mkd. T28S R4W S15 CCC BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel
post.

From this point, Cor. No. 1 of the Morning Star Placer, Mineral
Survey No. 979, bears N. $27^{\circ} 16' 00''$ W., .300 chs. dist., here-
inafter described.

Continue to desc. over NW. slope.

36.60 Lee Creek, 5 lks. wide, course W.; asc. over SE. slope.

39.260 The $\frac{1}{4}$ sec. cor. of secs. 14 and 15, perpetuated and recorded by
James W. Byron, Deputy County Surveyor, in 1957, and perpetuated
and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1966,
and perpetuated by George W. Plumb, Registered Land Surveyor No.
862, date unknown; monumented with an iron post, 1 $\frac{1}{2}$ ins. diam.,
firmly set 4 ins. below the surface of an abandoned road, 15 lks.
wide, bears NE. and SW., with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 28 S R 4 W
 $\frac{1}{4}$ 15 | 14
1957

from which the remains of an original bearing tree

A fir stump, 31 ins. diam., bears S. 40° W., 59 lks.
dist., with scribe marks $\frac{1}{4}$ S visible on an opened blaze.