

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 4 W., Willamette Meridian, Oregon

18681

CHAINS

and a bearing tree mkd. by Byron

A cedar, 22 ins. diam., bears S. 11° E., 48 lks.
dist., with healed blaze.

and a bearing tree mkd. by Plumb

A cedar, 13 ins. diam., bears N. 85½° E., 48 lks.
dist., with scribe marks ¼ S14 LS 862 BT.

and a new bearing tree

A hemlock, 17 ins. diam., bears S. 22° W., 64 lks.
dist., mkd. ¼ S15 BT.

N. 0° 08' 00" E., beginning new measurement.

Ascend over broken SE. slope.

0.70 Graveled road, 30 lks. wide, bears N. 50° E. and S. 50° W.

38.630 The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 28 S R 4 W
S 10 | S 11
S 15 | S 14
1958

from which the original bearing trees

A fir, 30 ins. diam., bears N. 30° E., 29 lks. dist.,
mkd. on the bark S11 T28S R4W

A cedar, 20 ins. diam., bears S. 5° W., 43 lks.
dist., with healed blaze.

A madrone, 24 ins. diam., bears N. 88° W., 66 lks.
dist., with healed blaze. (Record, 65 lks.)

and a bearing tree mkd. by Zirpel and Glenn

A fir, 23 ins. diam., bears N. 60° W., 40 lks.
dist., with healed blaze. (Record, 37½ lks.)

Alongside the iron post is another iron post, 1½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE 1957 COR SECS. 10 11 14 AND 15.

From the cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 1½ ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 28 S R 4 W
S 11 | S 12
S 14 | S 13
BLM 1965
1961

from which the remains of the original bearing trees

A burnt fir, 50 ins. diam., bears S. 7° E., 45 lks.
dist., with burned blaze.

A burnt fir snag, 62 ins. diam., bears N. 15° W.,
35 lks. dist., no marks remaining.