

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 4 W., Willamette Meridian, Oregon

18683

CHAINS	
	<p>A cedar, 7 ins. diam., bears N. 24$\frac{1}{4}$° W., 6 lks. dist., mkd. W 1/16 S11 BT.</p>
	<p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Ascend over E. slope.</p>
59.90	Spur, slopes S. 50° E.; desc. over SW. slope.
62.80	Bottom of descent, drains S.; asc. over broken SE. slope.
77.960	The cor. of secs. 10, 11, 14, and 15.
<p>Dependent Resurvey of a Portion of the Boundaries of Mineral Survey No. 979, T. 28 S., R. 4 W., Willamette Meridian, Oregon</p>	
<p>(Restoring the 1970 survey by George W. Plumb)</p>	
<p>From Cor. No. 1 of the Morning Star Placer, Mineral Survey No. 979, Oregon, monumented with an iron post, 1$\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above ground, from which the two remaining original bearing trees:</p>	
<p>A hemlock, 18 ins. diam., bears S. 51$\frac{1}{4}$° W., 43 lks. dist., with illegible scribe marks on a rotted blaze. (Record, S. 38$\frac{1}{2}$° W., 66$\frac{1}{2}$ lks.)</p>	
<p>A cedar, 33 ins. diam., bears N. 84$\frac{1}{4}$° W., 106 lks. dist., with healed blaze. (Record, N. 83$\frac{1}{2}$° W., 105 lks.)</p>	
<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 25 ins. in the ground, encompassing the iron post, with brass cap mkd.</p>	
<p>T 28 S R 4 W S 15 C 1 MS 1991</p>	
<p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is 20 lks. S. of Lee Creek, 5 lks. wide, course N. 80° W. S. 27° 16' 00" E., on line 1-2 of the Morning Star Placer.</p> <p>Ascend over broken NW. slope, through heavy timber and dense undergrowth.</p>	
0.300	A crossing closing cor. for secs. 14 and 15, hereinbefore described.
<p>From this point, the $\frac{1}{4}$ sec. cor. of secs. 14 and 15, bears N. 0° 19' 00" W., 3.110 chs. dist., hereinbefore described.</p>	
2.70	Graveled road, 20 lks. wide, bears N. 60° E. and S. 60° W.
4.20	Graveled road, 30 lks. wide, bears N. 65° E. and S. 65° W.
8.57	At this point, a cedar stump, 34 ins. diam., described in Mineral Survey No. 979.