

# County Surveyor's Record, Douglas County, Oregon

18684

Dependent Resurvey of a Portion of the Boundaries  
of Mineral Survey No. 979,  
T. 28 S., R. 4 W., Willamette Meridian, Oregon

**CHAINS**

8.710 Corner No. 2 of the Morning Star Placer, Mineral Survey No. 979, Oregon, monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, from which the remains of the original bearing trees:

A yew, 18 ins. diam., bears N. 80° W., 54 lks. dist., with scribe marks MS 2 979 BT visible on a partially healed blaze. (Record, hemlock)

A root hole, bears N. 55° W., 31 lks. dist., with a down, burnt fir alongside, 15 ins. diam., with no remaining marks.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

	T 28 S
MS	R 4 W
C 2	S 14
	1991

from which one new bearing tree

A fir, 9 ins. diam., bears N. 88½° E., 30 lks. dist., mkd. X at breast height and BT at the base.

Deposit white "DEEP-1" magnetic marker and iron post at base of stainless steel post.

S. 62° 54' 00" W., on line 2-3 of the Morning Star Placer.

Descend over NW. slope, through scattering timber and dense undergrowth.

4.270 A crossing closing cor. for secs. 14 and 15, hereinbefore described.

From this point, the cor. of secs. 14, 15, 22, and 23, bears S. 0° 19' 00" W., 26.730 chs. dist., hereinbefore described.

Cross a broken NW. slope.

9.20 Graveled road, 20 lks. wide, bears N. 10° W. and S. 10° E.

20.50 Ravine, drains N.35° W.; asc. over NE slope.

22.570 Corner No. 3 of the Morning Star Placer, identical with Cor. No. 4 of the Evening Star Placer, Mineral Survey No. 979, Oregon, monumented with an iron post, 1½ ins. diam., firmly set, projecting 2 ins. above ground, from which the original bearing trees:

A fir, 15 ins. diam., bears N. 11¼° E., 27 lks. dist., with healed blaze. (Record, N. 12¼° E., 25½ lks.)

A fir, 38 ins. diam., bears S. 58½° W., 53½ lks. dist., with healed blaze.

A fir, 18 ins. diam., bears N. 73¾° W., 26 lks. dist., with healed blaze. (Record, N. 72½° W.)

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, encompassing the iron post, with brass cap mkd.