

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the South Boundary,
T. 28 S., R. 5 W., Willamette Meridian, Oregon

18691

CHAINS

39.920

Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 28 S R 5 W
 $\frac{1}{4}$ S 35
S 2
T 29 S R 5 W
1988

from which

A fir, 12 ins. diam., bears S. 40° E., $8\frac{1}{2}$ lks. dist.,
mkd. $\frac{1}{4}$ S2 BT.

A fir, 10 ins. diam., bears N. 60° W., 13 lks. dist.,
mkd. $\frac{1}{4}$ S35 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Continue over broken SE. slope.

45.50

Graveled road, 30 lks. wide, bears N. 75° E. and S. 75° W.

56.40

Graveled road, 25 lks. wide, bears N. 20° W. and S. 20° E., on top of spur, slopes S. 20° E.; desc. over SW. slope.

59.880

Point for the W $\frac{1}{16}$ sec. cor. of secs. 2 and 35.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

W $\frac{1}{16}$ S 35
S 2
1988

from which

A fir, 18 ins. diam., bears N. 34° E., $27\frac{1}{2}$ lks. dist.,
mkd. W $\frac{1}{16}$ S35 BT.

A fir, 4 ins. diam., bears S. 30° E., $23\frac{1}{2}$ lks. dist.,
mkd. X at breast height and BT at the base.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Continue over SW. slope.

64.60

Ravine, drains SE.; asc. over broken SE. slope.

79.840

Point for the cor. of secs. 2, 3, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 28 S R 5 W
S 34 | S 35
S 3 | S 2
T 29 S R 5 W
1988

from which

A cedar, 29 ins. diam., bears N. $55\frac{1}{4}^\circ$ E., 54 lks. dist.,
mkd. T28S R5W S35 BT.