

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the South Boundary,  
T. 28 S., R. 5 W., Willamette Meridian, Oregon

18693

**CHAINS**

An oak, 16 ins. diam., bears N. 89 $\frac{1}{4}$ ° W., 357 lks. dist., with healed blaze.

and a witness cor. established by Byron

An iron post, 1 $\frac{1}{2}$  ins. diam., projecting 16 ins. above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T28S R5W  $\frac{1}{4}$  S WC S34 S3 T29S 1961, bears South, 0.150 chs. dist., located in a wire fence line, extending E. and W.

At the corner point

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 38 ins. in the ground, with top 10 ins. below the surface, with brass cap mkd.

T 28 S R 5 W  
 $\frac{1}{4}$  S 34  
S 3  
T 29 S R 5 W  
1988

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post. The corner is located in an open field.

S. 89° 18' 30" W., beginning new measurement.

Ascend over broken SE. slope, through scattering timber and undergrowth.

5.20 Spur, slopes SW.; desc. over NW. slope.

18.10 Graveled road, 20 lks. wide, bears N. 60° E. and S. 60° W.

28.30 Spur, slopes NW.; continue to descend over SW. slope.

40.250 The cor. of secs. 3, 4, 33 and 34, perpetuated and recorded by G.G. Stewart, Deputy County Surveyor, in 1922, from original evidence no longer in existence, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1961, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
T 28 S R 5 W  
S 33 | S 34  
S 4 | S 3  
T 29 S  
1961

from which the remains of the bearing trees mkd. by Stewart

A fir snag, 23 ins. diam., bears N. 35 $\frac{1}{4}$ ° E., 12 lks. dist., with rotted and burned blaze.

A fir snag, 20 ins. diam., bears S. 29° E., 32 lks. dist., no visible marks.

A fir snag, 28 ins. diam., bears N. 41 $\frac{1}{2}$ ° W., 62 lks. dist., with healed blaze.

and the remains of the bearing trees mkd. by Byron

A root hole, bears N. 8° E., 84 lks. dist., alongside of which is a down fir, 17 ins. diam., with scribe marks T28S R5W S34 CS visible on a partially healed blaze.