

# County Surveyor's Record, Douglas County, Oregon

18694

Dependent Resurvey of a Portion of the South Boundary,  
T. 28 S., R. 5 W., Willamette Meridian, Oregon

**CHAINS**

A fir, 25 ins. diam., bears S. 79 $\frac{1}{2}$ ° W., 62 lks. dist.,  
with healed blaze.

The corner is located on a SW. slope, 16 lks. NE. of the corner  
of fences extending E., W. and N.

Dependent Resurvey of a Portion of the East Boundary,  
T. 28 S., R. 5 W., Willamette Meridian, Oregon

(Restoring the survey by James E. Freeman, in 1851,  
the retracement by William H. Byars, in 1881,  
and the resurvey by G. Steven Popken, in 1974)

From the  $\frac{1}{4}$  sec. cor. of secs. 25 and 30, on the E. bdy. of the  
Tp., perpetuated and recorded by Bruce A. Shaner, Registered Land  
Surveyor No. 430, in 1964, monumented with an iron rod, 5/8 in.  
diam., firmly set, projecting 3 ins. above ground.

from which the remains of an original bearing tree

A rotted and burnt madrone stump, 26 ins. diam., bears  
S. 75° W., 15 lks. dist., no marks visible on a burned  
out blaze.

and the remains of the bearing trees mkd. by Shaner

A sawed and burnt fir stump, 39 ins. diam., bears  
S. 41 $\frac{1}{2}$ ° E., 38 $\frac{1}{2}$  lks. dist., with scribe mark S  
visible on a burned blaze.

A root hole, bears N. 56° W., 18 lks. dist., with a  
down fir alongside, 22 ins. diam., with a burned blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 14 ins.  
in the ground, directly over the iron rod, with brass cap mkd.

T 28 S  
R 5 W R 4 W  
 $\frac{1}{4}$   
S 25 | S 30  
1988

from which new bearing trees

A fir, 14 ins. diam., bears N. 3 $\frac{1}{2}$ ° E., 77 lks. dist.,  
mkd.  $\frac{1}{4}$  S30 BT.

A fir, 6 ins. diam., bears N. 29° W., 33 lks. dist.,  
mkd.  $\frac{1}{4}$  S25 BT.

N. 0° 19' 00" W., bet. secs. 25 and 30., marking and blazing the  
true line.

Descend over a steep NE. slope, through a recently logged and  
burned area.

5.30 Creek, 5 lks. wide, course SE.; asc. over SW. slope.

20.060 The N 1/16 sec. cor. of secs. 25 and 30, established and recorded  
by Bruce A. Shaner, Registered Land Surveyor No. 430, in 1964, and  
is accepted as the corner, monumented with an iron rod, 5/8 in.  
diam., firmly set, projecting 5 ins. above the ground.

from which the remains of bearing trees mkd. by Shaner