

# County Surveyor's Record, Douglas County, Oregon

18696

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 5 W., Willamette Meridian, Oregon

| CHAINS |   |
|--------|---|
|        | <p>(Restoring the survey by Robert Elder and Henry S. Gile, in 1853 and the survey by Addison R. Flint and L.L. Williams, in 1871)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp. N. 0° 34' 00" E., bet. secs. 35 and 36, marking and blazing the true line.</p> <p>Ascend over SW. slope, through scattering timber and dense undergrowth, along a barbed wire fence.</p>   |
| 25.80  | Spur, slopes S. 50° E.; desc. over NE. slope.   |
| 37.70  | Ravine, drains S. 30° E.; asc. over SE. slope.  |
| 39.570 | <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 35 and 36, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1961, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE<br/>T 28 S R 5 W<br/><math>\frac{1}{4}</math> S 35   S 36<br/>1961</p> <p>from which an original bearing tree</p> <p style="padding-left: 40px;">An oak, 19 ins. diam., bears N. 70° W., 231 lks. dist., with healed blaze. (Record, N. 75° W., 225 lks.)</p> <p>and bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A fir, 44 ins. diam., bears N. 19° E., 97 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 59° W., 159 lks. dist., with healed blaze.</p> <p>The corner is located at the corner of barbed wire fences extending W. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 20' 00" E., beginning new measurement.</p> <p>Ascend over SE. slope.</p> |
| 7.30   | Spur, slopes E.; desc. over NE. slope.  |
| 20.20  | Creek, 5 lks. wide, course S. 50° E.; asc. over broken SE. slope.   |
| 28.70  | Graveled road, 20 lks. wide, bears N. 80° W. and S. 80° E.  |
| 39.650 | <p>The cor. of secs. 25, 26, 35 and 36, perpetuated and recorded by John H. Markham Jr., Registered Engineer No. 2880, in 1949, further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1961, and further perpetuated and recorded by Bruce A. Shaner, Registered Land Surveyor No. 430, in 1964, monumented with an iron pipe, 1 in. diam., firmly set, projecting 10 ins. above ground, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A root hole, bears N. 45° E., 105 lks. dist., with a down ash alongside, 25 ins. diam., with scribe mark R visible on an open rotted blaze.</p> <p style="padding-left: 40px;">A madrone snag, 40 ins. diam., bears S. 22<math>\frac{1}{2}</math>° E., 121 lks. dist., with scribe marks BT visible on a partially healed blaze. (Record, S. 20° E., 125 lks.)</p>  |