

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 5 W., Willamette Meridian, Oregon

18697

**CHAINS**

A madrone, 46 ins. diam., bears S. 64° W., 126 lks. dist., with illegible scribe marks visible on the opened original blaze and illegible scribe marks visible on a partially healed blaze made by Shaner. (Record, S. 50° W., 140 lks.)

and a bearing tree mkd. by Byron

A fir, 20 ins. diam., bears N. 35¼° E., 76 lks. dist., with healed blaze.

and a bearing tree mkd. by Shaner

An oak, 25 ins. diam., bears S. 56° E., 126 lks. dist., with healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 28 S R 5 W  
S 26 | S 25  
S 35 | S 36  
1988

from which new bearing trees

A fir, 8 ins. diam., bears S. 12½° W., 63 lks. dist., mkd. T28S R5W S35 BT.

A cedar, 8 ins. diam., bears N. 26¼° W., 67 lks. dist., mkd. T28S R5W S26 BT.

Deposit a white "DEEP-1" magnetic marker at the base and the iron pipe alongside the stainless steel post.

From the ¼ sec. cor. of secs. 25 and 36, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1961, monumented with an iron post, 1½ ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
T 28 S R 5 W  
¼ S 25  
S 36  
1961

from which the remains of an original bearing tree

A burnt fir snag, 44 ins. diam., bears N. 45° W., 57 lks. dist., with a burned blaze.

and a bearing tree mkd. by Byron

A fir, 24 ins. diam., bears S. 62° E., 55 lks. dist., with a burned blaze.

S. 88° 55' 00" W., bet. secs. 25 and 36.

Ascend over a broken NE. slope, through a recently burned area.

10.40 Spur, slopes S. 40° E., leave burned area; desc. over broken SW. slope, through scattering timber and dense undergrowth.

19.760 The W 1/16 sec. cor. of secs. 25 and 36, established and recorded by Burton W. Holt, Registered Land Surveyor No. 418, in 1981, and is accepted as the corner, monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above ground, from which bearing trees mkd. by Holt: