

County Surveyor's Record, Douglas County, Oregon

18698

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

A cedar, 28 ins. diam., bears N. $81\frac{1}{4}^{\circ}$ E., 36 lks. dist., with scribe marks W 1/16 S25 visible on a partially healed blaze.

A cedar, 20 ins. diam., bears S. $33\frac{1}{2}^{\circ}$ E., 60 lks. dist., with scribe marks W 1/16 S36 visible on a partially healed burned face.

At the corner point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.

W 1/16 S 25
 S 36
 1988

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

S. $88^{\circ} 51' 30''$ W., beginning new measurement.

Descend over broken SW. slope.

14.00 Creek, 2 lks. wide, course S. 30° E.; asc. over SE. slope.

16.10 Dirt road, 20 lks. wide, bears N. 35° W., and S. 35° E.

17.60 Spur, slopes S. 50° E.; desc. over SW. slope.

18.00 Creek, 3 lks. wide, course S. 10° E.; asc. over SE. slope.

19.760 The cor. of secs. 25, 26, 35 and 36.

N. $0^{\circ} 45' 00''$ W., bet. secs. 25 and 26.

Descend over NE. slope, through scattering timber and undergrowth.

0.85 Creek, 8 lks. wide, course S. 70° E.; asc. over SE. slope.

3.70 Dirt road, 30 lks. wide, bears N. 60° W. and S. 60° E.

19.780 The S 1/16 sec. cor. of secs. 25 and 26, established and recorded by Donald R. Martin, Registered Engineer No. 3900, in 1969, and is accepted as the corner, monumented with an iron rod, $\frac{5}{8}$ in. diam., firmly set, projecting 3 ins. above ground, from which bearing trees mkd. by Martin:

A cedar, 20 ins. diam., bears S. $53\frac{3}{4}^{\circ}$ E., 37 lks. dist., no marks visible on a partially healed burned blaze.

A cedar, 12 ins. diam., bears N. $40\frac{1}{2}^{\circ}$ W., 64 lks. dist., no marks visible on a partially healed burned blaze.

At the corner point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

S 1/16
S 26 | S 25
 1988

Deposit a white "DEEP-1" magnetic marker at the base and the iron rod alongside the stainless steel post.

The corner is located N. 20° E., 8 lks. dist., from the head of a spring, 1 lk. wide, course S.
