

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 5 W., Willamette Meridian, Oregon

18699

CHAINS	
	N. 0° 35' 30" W., beginning new measurement.
	Ascend over broken SE. slope, through a recently burned area.
12.80	Creek, 3 lks. wide, course S. 20° E.; continue to ascend over broken SE. slope.
19.755	The $\frac{1}{4}$ sec. cor. of secs. 25 and 26, perpetuated and recorded by Bruce A. Shaner, Registered Land Surveyor No. 430, in 1964, determined from the remains of the original bearing trees: <p style="margin-left: 40px;">A root hole, bears S. 34<math>\frac{1}{4}</math>° E., 90 lks. dist., with a down cedar alongside, 16 ins. diam., with an opened burned blaze. (Record, S. 35° E.)</p> <p style="margin-left: 40px;">A fir, 28 ins. diam., bears S. 36° W., 68 lks. dist., with healed blaze. (Record, S. 32° W.)</p> <p style="margin-left: 40px;">and a bearing tree mkd. by Shaner</p> <p style="margin-left: 40px;">A cedar, 18 ins. diam., bears N. 34<math>\frac{1}{2}</math>° E., 115 lks. dist., with a partially healed burned blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 28 S R 5 W</p> <p style="margin-left: 40px;">†</p> <p style="margin-left: 40px;">S 26   S 25</p> <p style="margin-left: 40px;">1988</p> </div> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 20px auto;"/>
	N. 0° 20' 30" W., beginning new measurement.
	Ascend over broken SE. slope.
0.50	Wire fence, bears N. 60° E. turning N. and S. 60° W. turning W.
9.40	Slope changes to SW., leave burned area; continue to ascend.
19.95	Wire fence, bears E. and W.; enter open pastureland.
19.975	Point for the N 1/16 sec. cor. of secs. 25 and 26.
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	<p>N 1/16</p> <p>S 26   S 25</p> <p>1988</p>
	from which
	An oak, 27 ins. diam., bears S. 89° E., 163 lks. dist., mkd. N 1/16 S25 BT.
	An oak, 20 ins. diam., bears S. 76° W., 118 lks. dist., mkd. N 1/16 S26 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Continue over open SW. slope.